## **ETHNIC CUISINE**



#### Non-Stick Perforated Pizza Pan

art.	Dia	Height	Lbs
41729-30	11 3/4"	1/2"	0.7
41729-34	13 %"	1/2"	1.0

A staple in any pizza kitchen, professional perforated baking sheets are also great for home use. The perforations ensure that the heat of the oven reaches the crust for a crispy finish, and the non-stick coating ensures an easy-release of food. PTFE and PFOA-free, and dishwasher-safe.



Baking Pan	, Blue S	teel	
art.	Dia	Height	Lbs
11742-16	6 1/4"	1 3/8"	0.4
11742-18	7 1/8"	1 3/8"	0.5
11742-20	7 %"	1 3/8"	0.6
11742-22	8 %"	1 3/8"	0.7
11742-24	9 1/2"	1 3/8"	0.8
11742-26	10 1/4"	1 3/8"	0.9
11742-32	12 %"	1 3/8"	1.2
11742-36	14 1/8"	1 3/8"	1.6
11742-40	15 ¾"	1 3/8"	1.8
11742-45	17 ¾"	1 3/8"	2.2

This pan has flared sides and is typically used to make genoise and sponge cake, although it is also suited for baking pizza. Its relatively shallow depth keeps contents compact and moist, which allows quick heating and prevents overdrying. This cake pan is made of blue steel, enhancing browing. It also has rolled edges.

2.6



### Baking Sheet, Blue Steel

art.	Width	Length	Height	Lbs	• •
41745-30	9"	11 3/4"	1 1/8"	1.3	
41745-35	11"	13 ¾"	1 1/8"	1.8	
41745-40	11 3/4"	15 ¾"	1 1/8"	2.2	
41745-50	13 ¾"	19 5/8"	1 1/8"	3.0	
41745-60	15 ¾"	23 %"	1 1/8"	4.0	
41745-65	17 ¾"	25 %"	1 1/8"	4.8	

The relatively high, flared edges of the baking sheet are suited for baking and browning large, dense dough products. The sheet allows for full exposure to the heat of the oven. It is made of  $\frac{1}{16}$ " thick, black steel.



## Baking Sheet, 90° Sides, Aluminized Steel

11742-50 19 5%" 1 3%"

art.	Width	Length	Height	Lbs
41746-60	15 ¾"	23 5/8"	3/4"	3.8





# Sponge Cake Pan, Splayed Sides, Aluminized Steel

art.	Width	Length	Height	Lbs
41751-30	9"	11 ¾"	1 1/8"	1.3
41751-35	11"	13 ¾"	1 1/8"	1.7
41751-40	11 ¾"	15 ¾"	1 1/8"	2.1
41751-60	15 ¾"	23 %"	1 1/8"	3.9
41751-65	17 3/4"	25 %"	1 1/8"	4.5



#### Baking Sheet, 45° Sides, Aluminum

art.	GN	Width	Length	Lbs
41744-32	1/1	12 ¾"	20 %"	1.6
41744-53	2/1	25 %"	20 %"	3.2
41744-60	_	15 ¾"	23 5/8"	2.2