

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

# Undercounter Refrigerator-Extra Deep

Side Mount Undercounters J Series

Model: JUR-93D-N



## \_\_\_ FEATURES & BENEFITS =\_\_

- Digital temperature control & monitor system Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.
- Hydrocarbon refrigerants (R-290) With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- Side mount compressor unit With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our front air intake feature also allows this model to be highly efficient in narrow spaces.
- Stainless steel exterior The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. The J series adds a touch of style to the most refined setting.

LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Ergonomically designed doors Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 39°F for the best in food preservation













Model	Swing Doors	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H <sup>†</sup> (inches)
JUR-93D-N	3	30	6	1/2+	5.1	550	93 x 321/4 x 30

# Undercounter Refrigerator - Extra Deep

# Model: JUR-93D-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	NEMA 5-15P			
Full Load Amperes	5.1			
Compressor HP	1/2+			
Cord Length (ft.)	9			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	30			
Ext. Length Overall (in.)	93 (2362mm)			
Ext. Depth Overall (in.)*	321/4 (820mm)			
Ext. Height Overall (in.)†	30 (764mm)			
# of Doors	3			
# of Shelves	6			
Shelf Size (L x D) (in.)	237/8 x 251/2 , 257/8 x 251/2			
Net Weight (lbs.)	511			
Gross Weight (lbs.)	550			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 1" for rear spacers.

† Height does not include 6-1/4" for caster height.

#### 2 Year Parts and Labor Warranty WARRANTY: **Additional 3 Year Warranty on Compressor**


### STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system
- · 4" dia. swivel casters with locks on the front set
- \*\* Lead time applies. Please contact your sales representative for more details to order.


### OPTIONAL ACCESSORIES

- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Door lock: lead time applies. Please contact your sales representative for more details to order.


#### **PLAN VIEW** (unit: inch)



**TOP VIEW** 



**FRONT VIEW** 



Ver.20250807













■ Turbo Air: 800-627-0032 ■ Bake Tech: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002





