





GUIDE FOR SELECTING AMCO® CASTERS



Here is a simple system to take the guesswork out of selecting the best caster for most every type of need. The below worksheet assigns points to the key factors to consider for caster selection:

average weight of load, floor surface the casters will typically roll over, and the average operating temperature of the environment. Casters for special applications are also available.

Load

Weight of Cart..... lbs.
Average Weight of Load..... lbs.
Total Load Weight..... lbs.
Under 500 lbs. - 1 point
Over 500 lbs. - 3 points

Surface

Carpet - 1 point Concrete - 3 points
Steel - 3 points Asphalt Tile - 2 points
Quarry Tile - 4 points

Operating Temperature

Room Temperature - 1 point
Walk In Cooler - 2 points
Walk In Freezer - 5 points
Blast Freezer - 6 points

Total Points

Total points provide a guide for selecting wheel and tire material:

1 to 4 points: Soft • 5 to 8 points: Hard • 9 points or more: Urethane

Caster Diameter Recommendations:

Occasional Movement: 3" Dia. • General Purpose: 5" Dia. • Extremely Heavy Loads: 6" Dia.

Swivel Cat. No.	Swivel/Brake Cat. No.	Dia. in.	Face in.	Wheel Type	Tire Type	Capacity Each lbs.
HC3S	HC3B	3	1 1/4	Soft	None	220
AC1S	AC1B	5	1 1/4	Hard	None	280
AC2S	AC2B	5	1 1/4	Plastic	Urethane	300
AC3S	AC3B	5	1 1/4	Soft	None	190
AC4S	AC4B	6	1 1/4	Hard	None	300
AC5S	AC5B	6	1 1/4	Steel	Urethane	450
AC6S	AC6B	6	1 1/4	Soft	None	220
AC7S	AC7B	5	1 1/4	Plastic	Urethane	250
AC8RS	-	5	1 1/4	Plastic	Urethane	250

AC3 and AC7 also available in rigid models. AC8RS converts from rigid to swivel with the touch of the toe

AMCO®
A Leggett & Platt COMPANY