












# Specifying Your ELECTRICAL NEEDS

## Receptacle Configurations

 5-15R	 5-20R	 5-30R	 5-50R
 6-15R	 6-20R	 6-30R	 6-50R
	 14-20R	 14-30R	 14-50R

# Adding Your ACCESSORIES

## False Bottoms

- 300 series stainless steel
- Maintains ice longer
- 1" (2.5 cm) above well bottom
- Perforated for easy draining



ITEM #	DESCRIPTION
36913-2	Perforated false bottom, combination hot/cold food station
36914-2	Perforated false bottom, 46" (116.8 cm) cold food station
36915-2	Perforated false bottom, 60" (152.4 cm) cold food station
36916-2	Perforated false bottom, 74" (188 cm) cold food station
98855-5	Perforated false bottom, 88" (224 cm) cold food station

## Storage Modules

- 300 series stainless steel
- Available with 34" (86.4 cm) high bases only
- With or without doors; key lock for sliding doors standard
- Opening height of module is: 16½" (42 cm)
- Depth: 25½" (64.8 cm)
- Sizing may vary based on unit size and modifications



DESCRIPTION	WIDTH IN (CM)	ITEM# W/ DOORS	ITEM# W/O DOORS
Fits 3-well hot, 60" (152.4 cm) cold, 46" (116.8 cm) beverage	24 (61)	36930	36931
Fits 4-well hot, 46" (116.8 cm) utility, 74" (188 cm) cold, 60" (152.4 cm) beverage	36 (91.4)	36936	36937
Fits 5-well hot, 60" (152.4 cm) utility, 74" (188 cm) beverage	50 (127)	36938	36939
Fits 6-well hot, 74" (188 cm) utility station	64 (162.6)	36940	36941
Fits 88" (224 cm) utility station	64 (162.6)	36938-2	36939-2