DUNNAGE RACKS

- Designed to meet the minimum height restrictions of health departments
- Engineered to support heavy loads

Dunnage Racks with Grid

- Includes four 14" (355 mm) posts, one channel dunnage shelf,
 3-sided frame and wire grid
- Load rated to 2,000 lbs (907 kg) for racks up to 48" long
- 60" long racks load rated to 1,200 lbs (544 kgs)
- Height: 14"

Plating Plus™	Gold Bond®	WxLxH		Wt.	
Model No.	Model No.	(ln.)	(mm.)	(Lbs.)	(Kg.)
DR336C	DR336Y	18 x 36 x 14	457 x 914 x 355	34	15.6
DR348C	DR348Y	18 x 48 x 14	457 x 1219 x 355	42	19.3
DR360C	DR360Y	18 x 60 x 14	457 x 1524 x 355	48	22
DR536C	DR536Y	24 x 36 x 14	610 x 914 x 355	42	19.4
DR548C	DR548Y	24 x 48 x 14	610 x 1214 x 355	53	23.6
DR560C	DR560Y	24 x 60 x 14	610 x 1524 x 355	62	28



Dunnage Rack with Grid DR336Y

Mobile Dunnage Racks

- Includes four 8" (222 mm) posts, one channel dunnage shelf,
 3-sided frame, wire grid and four 5" (127 mm) diameter polyurethane casters (2 swivel and 2 swivel with brake)
- Load rated to 600 lbs
- Height: 14"

Plating Plus™	Gold Bond®	WxLxH Wt.		t.	
Model No.	Model No.	(ln.)	(mm.)	(Lbs.)	(Kg.)
MDR336C	MDR336Y	18 x 36 x 14	457 x 914 x 355	42	19.3
MDR348C	MDR348Y	18 x 48 x 14	457 x 1219 x 355	50	23
MDR536C	MDR536Y	24 x 36 x 14	610 x 914 x 355	48	22
MDR548C	MDR548Y	24 x 48 x 14	610 x 1219 x 355	54	24



Mobile Dunnage Rack MDR348Y

Wire Grid Cover for Platforms and Dunnage Racks

- Typical spacing between wires is 4" x 4"
- Fits both ISS and AMCO dunnage racks

	WxL		Wt.	
Model No.*	(ln.)	(mm.)	(Lbs.)	(Kg.)
DG336	19 x 37	483 x 940	12	5.5
DG348	19 x 49	483 x 1245	13	5.9
DG360	19 x 61	483 x 1549	19	8.6
DG536	25 x 37	635 x 940	13	5.9
DG548	25 x 49	635 x 1245	18	8.2
DG560	25 x 61	635 x 1549	21	9.5

^{*}Select a finish. Add suffix to model number

Finish	Suffix
Plating Plus™	C
Grey Bond®	E
Gold Bond®	Υ