

WORKTOP REFRIGERATOR

Model: SW48NBS-FB

Natural Refrigerant R-290 Model

48" Worktop Refrigerator with Solid Doors and 5½" Backsplash - Front Breathing



ENERGY STAR® Qualified Commercial Refrigerator

Stainless steel front, top and end panels, aluminum back and interior.



Options and Accessories

(upcharge and lead times may apply)

| | |
|---------------------------------------|---|
| Stainless steel interior | Door locks |
| Stainless steel back | Drawers in lieu of door (consult factory)** |
| Additional epoxy coated steel shelves | Special electrical requirements (consult factory) |
| Stainless steel shelves | Expansion valve system |
| Overshelves (single or double) | |

**Two Tier: (1) 12 x 18 x 6 pan per drawer or (1) ½ size x 6 & (1) ½ x 6 pans per drawer

Consult factory for other model configurations, options and accessories.

Continental
Refrigerator



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Smooth, polished chrome door handles

Spring loaded, self closing doors

Magnetic snap in Santoprene™ door gaskets

Heavy duty, epoxy coated steel shelves

Completely enclosed, vented and removable case back

3 ¾" casters

MODEL FEATURES

Electronic control, off cycle defrost

Field rehingeable doors

¹ R-290 refrigerant meets all federal and state regulatory requirements.

Front breathers are a unique, field assembled, bottom mounted ventilation system designed to allow cabinets to be flush against a wall or built into a counter to conserve space.

APPROVAL:

Model Specifications

DIMENSIONAL DATA

| | |
|---|--|
| Net Capacity (cubic feet) | 13.4 (379 l) |
| Width, Overall (inches) | 48 (1219 mm) |
| Depth, Overall (inches) (including handles & bumpers) | 32 ³ / ₁₆ (818 mm) |
| Height, Overall (inches) (including 3 ³ / ₄ " casters) | 39 ¹ / ₂ (1003 mm) |
| Shelf Area (square feet) | 6.8 (0.6 sq m) |
| Number of Shelves | 2 |
| Number of Doors | 2 |
| Interior Depth (inches) | See Drawing |
| Interior Height (inches) | 26 ¹ / ₄ (667 mm) |
| Interior Width (inches) | 44 (1118 mm) |

REFRIGERANT DATA

| | |
|-------------------------------|-----------------------------|
| Condensing Unit Size (H.P.) | ¹ / ₅ |
| R-290 Refrigerant Charge (oz) | 3.35 |
| Capacity (BTU per hour)* | 1390 |

ELECTRICAL DATA

| | |
|--|---------------------|
| Voltage (International) | 115/60/1 (220/50/1) |
| Total Amps (International) | 2.5 (1.3) |
| 10 ft. Cord/Plug [attached] (International) | Yes (No) |

SHIPPING DATA



| | |
|--------------------------|--|
| Weight (pounds) | 285 (135 kg) |
| Height - Crated (inches) | 47 ¹ / ₂ (1207 mm) |
| Width - Crated (inches) | 56 (1422 mm) |
| Depth - Crated (inches) | 37 ¹ / ₄ (946 mm) |

* Rating @ +25°F evaporator, 90°F ambient
Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug
(varies by country)

Model Plan Views



NOTE: For proper operation, the area under and in front of the cabinet **must** not be obstructed in any way.

Continental
Refrigerator

Toll-Free: 800-523-7138
Phone: 215-244-1400
Fax: 215-244-9579

539 Dunksferry Road
Bensalem, PA 19020
www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



PROUDLY
DESIGNED & ASSEMBLED
IN THE U.S.A.