



DB-130/200H 04/03/25 Item # 13131

			Qty:	
W x D x H	ADA Compliant <u>ठ</u>		AIA#:	
DB-130H 22" x 30" x 53"*			Features ► Ice dispensing area is ADA compliant	
DB-200H	DB-130H	DB-200H	1 5 1	
30" x 30" x 53" * *with 6" legs			Push-button single auger agitator	
Shipping Dimensions (DB-130H) 30 ^{1/2} " x 24" x 52"				
(DB-200H) 33" x 32 ^{1/4} " x 52"	0	©	 DB-130H Accommodates KM-350, KM-520, KM-660, or KMD-410 series cubers for 414 to 669 lbs. of ice per day (ice machines sold separately) 	
DB-130H Hotel/Motel Ice Dispenser			 Built-in 130 lbs. capacity* insulated polyethylene-lined ice storage bin 	
Shown with a KM-660MAJ (ice machine sold separately)			Push-button single auger agitator dispenses ice at 20 lbs. per minute	
DB-200H Hotel/Motel Ice Dispenser Shown with a KML-700MAJ			 DB-200H Accommodates KML Series, KM-350, KM-520, KM-660, series cubers for 380 to 756 lbs. of ice per day (<i>ice machines sold separately</i>) 	
(ice machine sold separately)	$\mathbf{I} + \mathbf{I}$		 Built-in 200 lbs. capacity* insulated polyethylene-lined ice storage bin 	
			Push-button single auger agitator dispenses ice at 13 lbs. per minute	
		Parts & Labor Barts & Labor Brite Machine Warnanty	Top kit may be required. See bin matrix in catalog. Warranty: 3 Year Parts & Labor on entire machine. Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries. * Capacity based on volume x 30 lb/ft ³ average density of ice.	

Item #: _ Project: _

	Model	Application Ice Storage Capacity	Measured Capacity Volume	Dispensing gear motor	Dispensing Rate	Voltage	Amperage	Net / Ship Weight (Ibs.)
	DB-130H	130 lbs.	3.7 ft ³	60W	20 lbs./min.	115V/60/1	1.4	178 / 195
1	DB-200H	200 lbs.	5.72 ft ³	60W	13 lbs./min.	115V/60/1	1.4	187 / 220

Operating Limits

- Ambient Temp Range 45 - 100°F 104 - 132V
- Voltage Range
- If GFCI is required, a GFCI breaker MUST be
- used in lieu of GFCI receptacle

Service

• Allow 6" (15 cm) clearance at rear and sides for ease of maintenance and/or service. More space is needed on left side for DB-130H (right side for DB-200H) of the dispensing bin to service the drive system.

Plumbing

• Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent

Vending

Pushbutton - Standard

Accessories

· HS-5749 - Water Dispenser Conversion Kit

Power cord not included. Must be hard-wired at site.



0 DB-130/200H Ο Item # 13131

04/03/25

