

# Coolers, Pass-Thru, One Zone, Front Serviced, Low Profile

CP1FL

CP1FL32, CP1FL36, CP1FL52, CP1FL60, CP1FL72, CP1FL84





4004503 Conforms to NSF/ANSI STD 7 and UL STD 471 Certified to CSA STD C22.2 No. 120 Listed to NSF Standard 7 for open food as a storage refrigerator

# Standard Features

- Self-contained
- Locking door(s)
- · LED interior lighting
- Heated mullion to minimize condensation
- Evaporator above compressor compartment to maximize storage capacity
- Two adjustable, coated-wire shelves per door section

# Configurable Options

## Temperature:

- Beer/Food 34°F to 40°F
- White wine 50°F to 55°F
- Red wine 60°F to 65°F

## **Refrigeration Compartment** Location:

Left or Right

# **Refrigeration Compartment** Cover Finish:

- Black vinyl-clad
- Stainless steel
- · Jeweled stainless
- Laminated
- Unlaminated

# Door Style & Finish (specify per • Blue door section):

Black vinyl-clad

- · Stainless steel
- · Jeweled stainless
- I aminated
- Unlaminated
- · Glass, black vinyl-clad
- · Glass, stainless steel
- Glass, jeweled stainless
- · Glass, laminated

# **Door Hinge Location (specify** for each door):

· Left or Right

## **Door Handle:**

- Signature
- Pull-tab
- Tube

# Top Style:

- No finished top
- Stainless top

# Left and Right Side Finish:

- · Black vinyl-clad
- Stainless steel

# **LED Lighting Style:**

- Bright white (7,000k)
- Warm white (3,500k)
- Amber (2,700k)

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444 www.glastender.com

Specifications subject to change without notice. For current specifications please visit our website.

Approval/Notes:

# Coolers - Pass-Thru, One Zone, Front Serviced, Low Profile

# **Specifications**

		CP1FL32	CP1FL36	CP1FL52	CP1FL60	CP1FL72	CP1FL84		
Dimensions	Length	32"	36"	52"	60"	72"	84"		
	Number of Sections	1	1	2	2	3	3		
	Door Opening	16"	20"	16"	20"	16"	20"		
Electrical	Electrical Supply	120V, 1 phase, 60 Hz, Dedicated 15 amp circuit is required							
	Full Load Amps	3.5	3.5	3.5	3.5	7.0	7.0		
	Plug Type	8 foot NEMA 5-15P grounded cord and plug which exits the back of refrigeration compartment*							
Refrigeration	Refrigerant	R290 - 125 grams, 3.88 oz., 0.24 pounds							
	Compressor	Reciprocating, 1/6 HP, 1300 BTUH, 0.11 Tons  Reciprocating, 1/4 2200 BTUH, 0.18							
	Heat Rejection	1430 BTUH	1430 BTUH	1430 BTUH	1430 BTUH	2867 BTUH	2867 BTUH		
Operating Range		34°F (1°C) to 65°F (18°C)							
Plumbing		Automatic condensate evaporator; no drain connection required †							
Weight Bearing Capacity		Countertops and other accessories should not exceed 200 pounds per door							

#### Materials

- Stainless steel parts include: exterior sub-top, interior, front of cabinet, hinges, hinge and lock brackets, and optional legs
- Black vinyl-clad steel parts include: standard sides, doors and compressor cover



· Galvanized steel parts include: back and bottom

† Building conditions outside the guidelines of ASHRAE 55 and ASHRE 62.1 may need to be plumbed to a drain.

# Capacities

	CP1FL32	CP1FL36	CP1FL52	CP1FL60	CP1FL72	CP1FL84
12 oz. bottles, cases	4.4	5.8	9.7	12.7	15.4	19.9
750ml wine bottles	35	42	66	90	106	137
1/2 barrel kegs	N/A	N/A	N/A	N/A	N/A	N/A
1/6 barrel kegs	N/A	N/A	N/A	N/A	N/A	N/A

# Coolers - Pass-Thru, One Zone, Front Serviced, Low Profile

# **Drawings**


## PLAN VIEW

1-1/8'

## 16" DOOR OPENING

# LENGTH (SEE TABLE) 18-1/2" DOOR SILL TO DOOR SILL


#### 20" DOOR OPENING




# **FRONT VIEW**

CONDENSING


UNIT COMPARTMENT




110°




# SIDE VIEW






SHOWN WITH OPTIONAL 6" LEGS

## STANDARD CABINET



# OPTIONAL LEGS AND CASTERS



Note: Available with compressor left or right. Compressor left model shown.

