

ROLL-IN COOLER RACKS | ALUMINUM

Rest easy knowing your prep work is safely supported by a Lakeside® roll-in cooler rack.

Aluminum material is economical and sturdy

- Extra gussets are welded in all corners to prevent alignment "racking" and distortion, so your trays stay level and steady
- Angle ledges hold full and 1/2 size sheet pans and 18" x 26" (457 x 660) or 13" x 18" (330 x 457)
- Universal ledges accept multiple sized trays and pans

FACTORY INSTALLED OPTIONS (PAGE 156):

- Corner Bumpers, non-marking gray rubber strip mounted to the corners of the unit's base. Note: This option adds 2" (51) to the width and depth of the unit.
- Vertical Bumpers, 8" (203) non-marking black rubber strip mounted on the uprights near unit's base. Note: This option adds 2" (51) to the width and depth of the unit.
- Pan Stop, aluminum strap welded to the rear of the unit
- Solid Base, solid aluminum sheet welded to the top of the base.
- Lake-Glide® 5" (127) casters with brakes (set of two)



Super strong welded corner braces prevent racking.



Model #8528



Model #8535



Freight Class: **125**
Ships in: **10** days or less!



ANGLE LEDGE ROLL-IN COOLER RACKS

Model	Fits Coolers	Full Size Pan Capacity	Ledge Description			Overall Size			Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
			Type	Width	Spacing	W	D	H		
8522	Low Type	18 ea.	Angle	1-1/2" (38)	3" (76)	20-1/2" (521)	26" 660	63" 1600)	42 (18.9)	22.8 (.62)
8528	Low Type	11 ea.	Angle	1-7/8" (48)	5" (127)	20-1/2" (521)	26" 660	64" 1626)	38 (17.1)	21.4 (.6)
8529	Low Type	18 ea.	Angle	1-7/8" (48)	3" (76)	20-1/2" (521)	26" 660	64" 1626)	48 (21.6)	21.4 (.6)
8547	Low Type	34 ea.	Channel	1/2" (13)	1-1/2" (38)	20-1/2" (521)	26" 660	64" 1626)	53 (23.9)	22.8 (.62)
8559	Low Type	38 ea.	Channel	1/2" (13)	1-1/2" (38)	20-1/2" (521)	26" 660	69" 1753)	56 (25.2)	25.7 (.71)

UNIVERSAL LEDGE ROLL-IN COOLER RACKS

Model	Fits Coolers	Ledge Description			Overall Size			Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
		# of	Type	Spacing	W	D	H		
8534	High Type	12 pairs	Universal Stepped Angle	4-1/2" (114)	24-1/2" (622)	25-1/4" 641	64-1/2" 1638)	90 (40.5)	24.4 (.6)
8535	High Type	13 pairs	Universal Stepped Angle	4-1/2" (114)	24-1/2" (622)	26" 660	70" 1778)	92 (41.4)	27.8 (.6)

Measurements in () denote metric millimeters, unless otherwise specified. Lake-Glide Casters: 5" (127) - All swivel, No-Mark® polyethylene, recessed plate mount.