

Aluminum Adjustable Cantilevered Shelving



Standard Features & Benefits

- ◆ Free standing unit, no setup required. Just take the unit out of the box, put the shelves in place, and start storing your items on the shelves
- ◆ No bolting to the walls
- ◆ No front posts increases your usable space
- ◆ 3 Types of shelves available - Solid, Channel, and Tubular. 5 Shelves can be added or removed
- ◆ removable bottom dunnage shelf.
- ◆ Up to 2800# load capacity per section
- ◆ Shelving clearance is 9 5/8"
- ◆ Standard Height is 72", custom height and shelving spacing is available
- ◆ *Meets NSF specification for use in walk in coolers and freezers*
- ◆ *Lifetime Guarantee Against Rust*

FRAME

SHELF



SHELF NOTCHES

Model:

- ☐ ACAF
- ☐ ACACS
- ☐ ACA
- ☐ ACAS

Job Name: _____

Qty: _____

Item: _____

814 Jordan Lane, Decatur, GA 30033
404-296-9080 1-800-810-9080 Fax: 404-296-3040

HELMAX
Equipment

Specifications:

CONSTRUCTION:

TUBULAR:

Model *ACA* - Constructed of 1½" square tube spacing welded horizontal on 4½" centers. Load capacity per shelf is 1500 lbs.

SOLID:

Model *ACAS* - Constructed of one piece .060 aluminum sheet welded in over tubular frame. Load capacity per shelf is 900 lbs.

CHANNEL:

Model *ACACS* - Constructed of 4" wide x 1¼" x .080 "E" channel style with center leg welded horizontally on approximately 2" centers, two channels on 18" spacing and 20" and three channels on 24" and 27" shelves. Load capacity per shelf is 1500 lbs.

UPRIGHTS:

Constructed of 2" x 4" heavy wall aluminum tubing sealed top and bottom. Front leg to be welded to upright allowing for 6" clearance and have adjustable foot. Legs will not extend beyond the front shelves.

To Lay Out Shelving:

Since there is no front post, nominal sizes are not needed. For example, a wall 16 feet 2 inches long could use (3) 60" sections. The shelving sections would be placed 3½" apart giving complete utilization of wall space.

For use in coolers and freezers with blowers lower than 80". We recommend under the blower a special height three tier shelving unit. This will keep the top two shelves level with the surrounding four tier shelving. This unit's overall height is 52" To order this shelving add /52 to the end of the model number for that section of shelving.

FRAME

MODEL	SIZE	
	DIM(LxDxH)	WGT
	IN	LB
20" DEEP SHELVING FRAME		
ACAF3620	36x20x72	49
ACAF4820	48x20x72	55
ACAF5420	54x20x72	60
ACAF6020	60x20x72	61
24" DEEP SHELVING FRAME		
ACAF3624	36x24x72	64
ACAF4824	48x24x72	75
ACAF5424	54x24x72	84
ACAF6024	60x24x72	86

SHELVES

CHANNEL	TUBULAR	SOLID	DIM(LxD)	WGT
MODEL	MODEL	MODEL	IN	LB
20" DEEP SHELVING UNITS				
ACACS3620	ACA3620	ACAS3620	36x20	10
ACACS4820	ACA4820	ACAS4820	48x20	12
ACACS5420	ACA5420	ACAS5420	54x20	13
ACACS6020	ACA6020	ACAS6020	60x20	14
24" DEEP SHELVING UNITS				
ACACS3624	ACA3624	ACAS3624	36x24	11
ACACS4824	ACA4824	ACAS4824	48x24	13
ACACS5424	ACA5424	ACAS5424	54x24	14
ACACS6024	ACA6024	ACAS6024	60x24	15

BASE DUNNAGE SHELF - TUBULAR

MODEL	SIZE	
	DIM(LxD)	WGT
	IN	LB
20" DEEP BOTTOM DUNNAGE SHELF		
ACB3620	36x20	10
ACB4820	48x20	12
ACB5420	54x20	13
ACB6020	60x20	14
24" DEEP BOTTOM DUNNAGE SHELF		
ACB3624	36x24	11
ACB4824	48x24	13
ACB5424	54x24	14
ACB6024	60x24	15



814 Jordan Ln. Decatur, GA 30033

404-296-9080 1-800-810-9080 Fax: 404-296-3040

www.kelmax.com