

# USA FOODSERVICE

# TRM4L-YN-BLK-WHT-1BLKLLLL-4

True Retail Merchandiser • 4-Door • Low Temp – In Line Left Panel/Finished Right Panel – Black Exterior – White Interior Aluminum Frame Black Doors • All Left Door Hinge – 4000K LED Lighting

 Project Name
 Location
 Item #
 Quantity
 Model #
 AIA #
 SIS #

# **FEATURES**

- R290 natural refrigerant.
- Self-contained factory-charged and sealed refrigeration system.
- · Interior finish: White.
- · Exterior finish: Black.
- Temperatures of -10°F to 6°F (-23.3°C to -14.4°C).
- · Self-cleaning technology.
- NSF/ANSI standard 7 compliant for the storage and/or display of packaged products only.
- 4000k color temperature LED interior lighting.
- Total of 20 (5 per door) adjustable, solid white powder coated cantilever shelves 30W" x 25D" (762mmW x 635mmD).
- Energy Star® listed.
- Cabinet fitted with leg levelers. Utilizing True's patented True Level leveling system™.
- "Low-E" triple pane thermal insulated glass doors.
- Stay-Open door feature.

# TRM SERIES







# PHYSICAL DATA

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest %" (millimeters rounded up to next whole number).

LED Color	Usable Capacity LED Color (Cu. Ft.) # of			# of	CL 157	Cabinet Weight (lbs.) (kg)		# of Ref.	(lbs.) (kg)		Interior Dimensions (inches) (mm)		Cabinet Dimensions (inches) (mm)				Interior		Ref Charge			Max. Temp	
Temperature					Shelf Type Design		Uncrated	Decks ≠		Uncrated	w	D	н	w	D†	н	1.0	Finish		(per deck)	Refrigerant		(°F) (°C)
4000k	154.4	4	Glass	20	Cantilever	1760	1512	3	480	375	123%	28	681/8	1271⁄4	38%	102	Black	White	Black	5.25oz	R290	-10°F	6°F
	4372					798	659		218	170	3126	709	1730	3231	987	2591	DIACK V	vviille	DIACK			-23.3°C	-14.4°C

- † Depth does not include 1½" (35 mm) for door handles.
- $\neq$  Refrigeration decks ship separately and individually.

# **ELECTRICAL & ENERGY DATA**

Specifications subject to change without notice.

Daily Energy Use	Energy Star	# of Ref.	Condenser	Total Rejected Heat	208-240V Volta	Cord Length‡ (total ft.)	
(Kwh/Day)	Certified			(Btu/h)	HP (Per Deck)	Total Amps	(total m)
33.58	Yes	3	Air Cooled	8471	11⁄4	19.6	10
							3.05

# NEMA Configuration



Unit completely pre-wired at factory and ready for final connection to a 208-240V-1PH-60Hz, cord and plug set included.





APPROVALS







AVAILABLE AT

8/25



# TRM4L-YN-BLK-WHT-1BLKLLLL-4

True Retail Merchandiser • 4-Door • Low Temp – In Line Left Panel/Finished Right Panel – Black Exterior – White Interior Aluminum Frame Black Doors • All Left Door Hinge – 4000K LED Lighting

## ADDITIONAL FEATURES

#### Design

- True's commitment to using the highest quality materials and energy efficient refrigeration systems provides the user with colder product temperatures and lower utility costs.
- Take advantage of the install flexibility, convenience, and efficiency of this self-contained case. Fit TRM's through 82" height and 41" wide openings, move the case into location, install the compact sealed condensing systems and plug it in. No refrigeration connections or technicians needed for install.
- The entire cabinet structure is built using high-density, polyurethane insulation that has zero ozone depletion potential.
- Refrigeration redundancy architecture helps prevent product loss.
- Patented True Level Leveling System™ for a quick install.

#### Refrigeration System

- Environmentally friendly R290 Natural Refrigerant system.
- Self-contained factory-charged and sealed refrigeration system.
- The True Dynamic Refrigeration Response System™ allows for quick product pull down where and when cooling demand is needed.
- · Refrigeration decks ship separately; installed onsite.
- Self-cleaning reverse condensing fan motor technology helps prevent condenser blockage.

- Plug-and-play electrical system for seamless installation (No refrigeration tech or electrician needed).
- · DOE and Energy Star Listed.
- NSF/ANSI standard 7 compliant for the storage and/or display of packaged products only.
- Cabinet designed for optimum performance in air-conditioned areas not to exceed 80°F ambient and 55% relative humidity.
- · High-efficiency variable speed compressor technology.

#### Shelving

 Total of 20 (5 per door) adjustable, solid white powder coated cantilever shelves 30"W x 25"D (762mmW x 635mmD).

#### Doors

- Self closing doors with stay open feature.
- "Low-E" triple pane thermal insulated glass door.
- Viewable glass height of 70" for maximum product display.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.
- · Right most door is field reversible.
- For all left hinge units (LLLL) the right most door is field reversible on NN and YN end panel models.
- For all right hinge units (RRRR) the left most door is field reversible on NN and NY end panel models.

#### **LED Lighting**

 4000k color temperature LED interior lighting, provides brilliant lighting throughout the cabinet.

#### **Electrical**


 Unit completely pre-wired at factory and ready for final connection to a 208-240V-1PH-60Hz, cord and plug set included.


## **Optional Features/Accessories**


(upcharge and lead times may apply)

- $\square$  Peg hook kit white (Includes 5 Peg Hooks and clear price tag holders)
- ☐ Peg hook kit Black (Includes 5 peg Hooks and clear price tag holders)
- ☐ Balloon guard kit
- ☐ Heated drain pan assembly
- ☐ Bottom sill product Id strip clear
- $\square$  Shelf product ID strip white
- ☐ Shelf product ID strip black
- ☐ Corner kit black
- ☐ Black or white cantilever shelves
- ☐ Black interior

## **PLAN VIEWS**







FRONT VIEW SIDE VIEW

TOP VIEW

Plan View Notes: Dimensions in brackets are in millimeters. • Depth does not include 1½" (35 mm) for door handles • Height does not include ½" (7 mm) for leg levelers.