

AQUATUFF™ WRAP & STOW™

The AquaTuff series with Wrap&Stow™ probes are the right choice when accuracy calibrated with a TRUE 0.9°F accuracy and probes can be replaced in the field heavy duty, patented probe can be stored safely alongside the unit housing.

Wrap & Stow probes can be replaced at your location and maintain a total

The 35340 AquaTuff includes an Intelligent Stabilization (ITS) feature that includes a memory function that can store up to 250 readings.

- ▶ **INDUSTRY LEADING 5-YEAR WARRANTY**
- ▶ **IPX7 WATERPROOF**
- ▶ **UNIQUE CABLE STORAGE CHANNEL**

Instruments



	35132	35135	35140	35232	35235	
	w/ DuraNeedle Probe	w/ Angled Surface Probe	w/ MicroNeedle Probe	w/ DuraNeedle	w/ Angled Surface Probe	
Temperature Range:	-100° to 500°F (-73° to 260°C)	-100° to 500°F (-73° to 260°C)	-100° to 500°F (-73° to 260°C)	-100° to 500°F (-73° to 260°C)	-100° to 500°F (-73° to 260°C)	
Accuracy:	±0.9°F (±0.5°C) total system accuracy	±0.5°F (±0.3°C)	±0.9°F (±0.5°C) total system accuracy	±0.9°F (±0.5°C) total system accuracy	±0.5°F (±0.3°C)	
Housing Material:	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic	
Resolution:	0.1°	0.1°	0.1°	0.1°/ 1° selectable	0.1°/ 1° selectable	
Hold:	No	No	No	Yes	Yes	
Backlight:	No	No	No	Yes	Yes	
Power:	(2) 1.5V AAA	(2) 1.5V AAA	(2) 1.5V AAA	(2) 1.5V AAA	(2) 1.5V AAA	
Battery Life:	1800 hours	1800 hours	1800 hours	1800 hours	1800 hours	
Auto Off:	10 min.	10 min.	10 min.	10 min.	10 min.	
Weight:	7 oz (199 g)	8 oz (227 g)	7 oz (199 g)	7 oz (199 g)	8 oz (227 g)	
Regulatory Listings:	CE NSF RoHS	CE RoHS	CE NSF RoHS	CE NSF RoHS	CE RoHS	
Warranty:	5 Year Instrument	5 Year Instrument	5 Year Instrument	5 Year Instrument	5 Year Instrument	
Probe Response Time:	1 second (Liquid)	2 seconds (Oiled Surface)	1 second (Liquid)	1 second (Liquid)	2 seconds (Oiled Surface)	