CAMBRO

Camshelving® Elements XTRA Series

High Density Storage Floor Track System High Density Mobile Starter Units 4 Vented or Solid Shelves

HEIGHTS	DEPTHS	LENGTHS
2	3	5
70 ¼"	18"	36" 54"
78 ¼"	21"	42" 60"
	24"	48"

• High Density Mobile Starter Units include:

2 factory assembled mobile post kits, 8 shelf traverses, shelf plates, 4 high density grooved casters, and 4 high density donut bumpers. Units ship complete in 1 box.

• High Density Full Track Kits include:

Aluminum raised tracks, steel joiners, stationary unit end plates and leveling feet, pan head screws, and star washers.

• High Density Track Extension Kits include:

Aluminum raised tracks, steel joiners, pan head screws and star washers.

Features & Benefits

- System composed of stationary starter units anchored to raised floor track system at each end with high density mobile units installed on tracks.
- Withstands storage temperatures from -36° to 190°F (-38° to 88°C).
 Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Impervious to moisture, chemicals, salt, food acids, and humidity.
- Posts and traverses are made of revolutionary, extremely strong composite material with a smooth, easy-to-clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Shelf traverse dovetails snap easily and quickly into place.
- High density donut bumpers offer added protection when maneuvering units back and forth on the track.
- Grooved track rails connect to bottom of stationary units with easy to install stainless steel hardware. No bolts, glue or drilling required.
- Aluminum tracks and stainless steel hardware are rust resistant.
 Track provides smooth and level surface for mobile units and is designed for easy cleaning.
- Removable polypropylene shelf plates have permanent, molded-in Camguard®, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria.
- Shelf traverses can be removed and adjusted easily at 4" (10,2 cm) increments.
- Recommend installing a stationary unit every 15' (4,6 m) of track to stabilize system.

Printed in USA. REV. 12/23

- Lifetime warranty against rust and corrosion.
- Available in 1 color Speckled Gray (480).

Project _	
Item No	
Quantity .	



Weight Bearing Capacity

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 24" - 48"
MOBILE UNIT	Unit only*	750 lbs.

^{*} Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 750 lbs.

Full Track and Extension Kits

CODE	DESCRIPTION	PACK
Full Track Kits		
CSMHDTK10	10' Track for 3 Mobile Units*	1
CSMHDTK12	12' Track for 4 Mobile Units*	1
CSMHDTK145	14.5' Track for 5 Mobile Units*	1
Track Extension Kits		
CSMHDTKE4	4.5' Track Extension	1
CSMHDTKE5	5' Track Extension	1
CSMHDTKE6	6' Track Extension	1

Color: Silver (000). *Based on 24" deep mobile units.

Track Extension Kits include: Track rails (1 set), rail joiners, and hardware to complete installation.

Approvals



Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

COMPONENT



Information and specifications are subject to change without notice. Please confirm at time of order.

Camshelving® Elements XTRA Series

High Density Storage Floor Track System High Density Mobile Starter Units 4 Vented or Solid Shelves



4-Shelf Vented High Density Mobile Units

HEIGHT

DEPTH

HEIGHT

DEPTH

DEPTH

Optional Accessories

☐ Shelf Divider Bars (Straight or Angled)

☐ Shelf Identification Tags

☐ Shelf Divider Panel

□ Shelf Rails ■ Wall Fastener

CODE	DIM. D x L x H
EXHD183670V4	18" x 36" x 70½"
EXHD184270V4	18" x 42" x 70½"
EXHD184870V4	18" x 48" x 70½"
EXHD185470V4	18" x 54" x 70½"
EXHD186070V4	18" x 60" x 70½"
EXHD213670V4	21" x 36" x 701/4"
EXHD214270V4	21" x 42" x 701/4"
EXHD214870V4	21" x 48" x 701/4"
EXHD215470V4	21" x 54" x 701/4"
EXHD216070V4	21" x 60" x 701/4"
EXHD243670V4	24" x 36" x 701/4"
EXHD244270V4	24" x 42" x 701/4"
EXHD244870V4	24" x 48" x 701/4"
EXHD245470V4	24" x 54" x 701/4"
EXHD246070V4	24" x 60" x 701/4"
CODE	DIM. D x L x H

CODE	DIM. D X L X II
EXHD183678V4	18" x 36" x 781/4"
EXHD184278V4	18" x 42" x 781/4"
EXHD184878V4	18" x 48" x 781/4"
EXHD185478V4	18" x 54" x 781/4"
EXHD186078V4	18" x 60" x 781/4"
EXHD213678V4	21" x 36" x 781/4"
EXHD214278V4	21" x 42" x 781/4"
EXHD214878V4	21" x 48" x 781/4"
EXHD215478V4	21" x 54" x 781/4"
EXHD216078V4	21" x 60" x 781/4"
EXHD243678V4	24" x 36" x 781/4"
EXHD244278V4	24" x 42" x 781/4"
EXHD244878V4	24" x 48" x 781/4"
EXHD245478V4	24" x 54" x 78½"
EXHD246078V4	24" x 60" x 781/4"

☐ Single Shelf Sheet Pan/Tray Rack

☐ Shelf Traverses (Single or Double)

☐ Single Shelf Security Cage


☐ Single Shelf Sheet Pan Rack

☐ Bottom Shelf Dunnage Stands

Printed in USA. REV. 12/23

Color: Speckled Gray (480).

Model No. Quantity



4-Shelf Solid High Density Mobile Units

4.011	CODE	DIM. D x L x H
18"	EXHD183670S4	18" x 36" x 70½"
DEPTH	EXHD184270S4	18" x 42" x 701/4"
DEI III	EXHD184870S4	18" x 48" x 70½"
	EXHD185470S4	18" x 54" x 70½"
04"	EXHD186070S4	18" x 60" x 70½"
71 "	EXHD213670S4	21" x 36" x 701/4"
DEPTH	EXHD214270S4	21" x 42" x 70½"
DEI III	EXHD214870S4	21" x 48" x 701/4"
	EXHD215470S4	21" x 54" x 701/4"
	EXHD216070S4	21" x 60" x 701/4"
24 "	EXHD243670S4	24" x 36" x 701/4"
DEPTH	EXHD244270S4	24" x 42" x 70½"
	EXHD244870S4	24" x 48" x 70½"
	EXHD245470S4	24" x 54" x 701/4"
	EXHD246070S4	24" x 60" x 701/4"
	CODE	DIM. D x L x H
18"	CODE EXHD183678S4	DIM. D x L x H 18" x 36" x 781/4"
18"		
18 " DEPTH	EXHD183678S4	18" x 36" x 781/4"
10	EXHD183678S4 EXHD184278S4	18" x 36" x 78½" 18" x 42" x 78½"
DEPTH	EXHD183678S4 EXHD184278S4 EXHD184878S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½"
10	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½" 18" x 54" x 78½"
21 "	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½" 18" x 54" x 78½" 18" x 50" x 78½"
DEPTH	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4 EXHD213678S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½" 18" x 54" x 78½" 18" x 60" x 78½" 21" x 36" x 78½"
21 "	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4 EXHD213678S4 EXHD213678S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½" 18" x 54" x 78½" 18" x 50" x 78½" 21" x 36" x 78½" 21" x 42" x 78½"
21 "	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4 EXHD213678S4 EXHD214278S4 EXHD214478S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½" 18" x 54" x 78½" 18" x 60" x 78½" 21" x 36" x 78½" 21" x 42" x 78½" 21" x 42" x 78½"
DEPTH 21" DEPTH	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4 EXHD213678S4 EXHD214278S4 EXHD214478S4 EXHD215478S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½" 18" x 54" x 78½" 18" x 60" x 78½" 21" x 36" x 78½" 21" x 42" x 78½" 21" x 42" x 78½" 21" x 48" x 78½"
21" DEPTH	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4 EXHD213678S4 EXHD214278S4 EXHD214478S4 EXHD215478S4 EXHD215478S4	18" x 36" x 78¼" 18" x 42" x 78¼" 18" x 48" x 78¼" 18" x 54" x 78¼" 21" x 36" x 78¼" 21" x 42" x 78¼" 21" x 48" x 78¼" 21" x 48" x 78¼" 21" x 54" x 78¼" 21" x 54" x 78¼"
DEPTH 21" DEPTH	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4 EXHD213678S4 EXHD214278S4 EXHD214478S4 EXHD215478S4 EXHD215478S4 EXHD215478S4 EXHD215478S4	18" x 36" x 78¼" 18" x 42" x 78¼" 18" x 48" x 78¼" 18" x 54" x 78¼" 21" x 36" x 78¼" 21" x 42" x 78¼" 21" x 42" x 78¼" 21" x 48" x 78¼" 21" x 54" x 78¼" 21" x 54" x 78¼" 21" x 54" x 78¼" 24" x 36" x 78¼"
21" DEPTH	EXHD183678S4 EXHD184278S4 EXHD184878S4 EXHD185478S4 EXHD186078S4 EXHD213678S4 EXHD214278S4 EXHD214878S4 EXHD215478S4 EXHD215478S4 EXHD244278S4	18" x 36" x 78½" 18" x 42" x 78½" 18" x 48" x 78½" 18" x 54" x 78½" 21" x 36" x 78½" 21" x 42" x 78½" 21" x 42" x 78½" 21" x 48" x 78½" 21" x 54" x 78½" 21" x 60" x 78½" 24" x 36" x 78½" 24" x 36" x 78½"

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.

Post Connectors: Reinforced polypropylene.

Shelf Plates: Reinforced polypropylene with Camguard™ antimicrobial.

Adjustable Foot: Reinforced nylon.

Traverse Dovetails: Reinforced nylon.

Post Connector Collar Wedge: Reinforced nylon.

High Density Caster: Polyolefin resin with zinc plated post.

Approvals



Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.





COMPONENT

Information and specifications are subject to change without notice. Please confirm at time of order.