



SHELVING

AMCO II® WIRE SHELVING



ITEM # _____ MODEL # _____ QTY: _____
 PROJECT: _____
 OPTIONS: ☐ YES _____ ☐ NO _____



Standard Features & Benefits

- ◆ Unique square post design uses 27% more steel providing greater strength and durability than typical round post systems
- ◆ Shelves come in 5 widths and 8 lengths
- ◆ Shelves up to 48" long support up to 1,000 lbs. (450 kg)
- ◆ Assembly is fast and easy with a one-piece shelf installation adapter — a collet that can be slipped on the post at any height
- ◆ Posts are notched on 2" centers to assure perfect shelf alignment every time
- ◆ 17% taller collar provides more strength and greater rigidity
- ◆ Solid 2-1/8" robotic welds provide more stability than the two spot welds used on round post systems
- ◆ Shelf wire averages 50% thicker than other systems providing greater shelf capacity and strength
- ◆ Shelves have solid edges instead of truss edges making them easier to clean and label
- ◆ Use add-on unit to continue a straight line of shelving, for right angles or for back-to-back shelving
- ◆ Frame is 12 gauge solid steel
- ◆ Choose finish or color by adding appropriate suffix to model number (see chart to the left)

*Select a finish. Add suffix to model number.

Finish	Suffix	Color	Suffix
Plating Plus™	CP	Black**	BK
Polygard® (Blue)	PG	White**	W
Stainless Steel	SS	Red**	R

**Minimum quantity must be ordered for shelving with color finishes. Any combination of shelves and posts must equal 100. (For example, 40 posts and 60 shelves.)

For SPG's complete product menu, visit www.spgusa.com or call 877.503.4SPG (4774)

EXPECT MORE
SPG
 STORAGE PRODUCTS GROUP

SHELVING

AMCO II WIRE SHELVING

Specifications

SHELVES

Shelves are constructed of .162" gauge crosswires spaced 1-1/16" on centers with 5/16" (.3125") cross-braces. Cross braces are welded at each end of 9/16" x 1-1/4" x .090" leg. Square tapered 1-3/4" high steel collars are welded at each corner and a series of .262" rebrace wires are welded to the underside of the 18", 21" and 24" wide shelves in lengths of 54" and longer. All contact points are welded.

POSTS

Posts are constructed of .065" thick square tubes notched every 2" on each corner. A nylon cap is installed on the top and a nylon housing for a 3/8" – 16 x 1-1/4" steel leveler is notched on the bottom. The leveler has a 7/8" hex head and a 3/4" threadless shoulder to eliminate deposits of mop strands and broom fibers.

ASSEMBLY

Four nylon tapered collets are packed with each shelf. The collets can be installed onto any notched position on the post. The tapered shelf collars mate to the tapered nylon collet to securely seat the shelf onto the post. No additional tools are needed for assembly.

Model No.*	W x L		Weight	
	(In.)	(mm.)	(Lbs.)	(Kg.)
12" Wide Shelves				
A1224	12¼ x 23¾	305 x 610	6½	2.9
A1230	12¼ x 29¾	305 x 760	7½	3.4
A1236	12¼ x 35¾	305 x 915	9	4.1
A1242	12¼ x 41¾	305 x 1065	10½	4.5
A1248	12¼ x 47¾	305 x 1220	12	5.4
A1254	12¼ x 53¾	305 x 1370	13½	5.9
A1260	12¼ x 59¾	305 x 1525	14	6.3
A1272	12¼ x 71¾	305 x 1830	15½	7
15" Wide Shelves				
A1524	15¼ x 23¾	380 x 610	7 ½	3.4
A1530	15¼ x 29¾	380 x 760	8½	3.9
A1536	15¼ x 35¾	380 x 915	10	4.5
A1542	15¼ x 41¾	380 x 1065	11½	5.2
A1548	15¼ x 47¾	380 x 1220	13½	6.1
A1554	15¼ x 53¾	380 x 1370	14½	6.6
A1560	15¼ x 59¾	380 x 1525	16	7.3
A1572	15¼ x 71¾	380 x 1830	19	8.6
18" Wide Shelves				
A1824	18¼ x 23¾	455 x 610	8½	3.6
A1830	18¼ x 29¾	455 x 760	9½	4.3
A1836	18¼ x 35¾	455 x 915	11	5
A1842	18¼ x 41¾	455 x 1065	13½	5.9
A1848	18¼ x 47¾	455 x 1220	15	6.8
A1854	18¼ x 53¾	455 x 1370	16½	7.5
A1860	18¼ x 59¾	455 x 1525	18	8.2
A1872	18¼ x 71¾	455 x 1830	21½	9.7
21" Wide Shelves				
A2124	21¼ x 23¾	535 x 610	9	4.1
A2130	21¼ x 29¾	535 x 760	10½	4.8
A2136	21¼ x 35¾	535 x 915	12	5.4
A2142	21¼ x 41¾	535 x 1065	15½	6.8
A2148	21¼ x 47¾	535 x 1220	17	7.7
A2154	21¼ x 53¾	535 x 1370	19½	8.8
A2160	21¼ x 59¾	535 x 1525	20½	9.3
A2172	21¼ x 71¾	535 x 1830	24	10.9
24" Wide Shelves				
A2424	24¼ x 23¾	610 x 610	10	4.5
A2430	24¼ x 29¾	610 x 760	12½	5.4
A2436	24¼ x 35¾	610 x 915	13½	6.1
A2442	24¼ x 41¾	610 x 1065	16½	7.5
A2448	24¼ x 47¾	610 x 1220	18½	8.4
A2454	24¼ x 53¾	610 x 1370	21½	9.5
A2460	24¼ x 59¾	610 x 1525	23	10.4
A2472	24¼ x 71¾	610 x 1830	27	12.2

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke

SPG International, LLC
11230 Harland Drive NE
Covington, GA 30014
877-503-4SPG (4774)

www.spgusa.com

The best names in the business
all have one thing in common.

EXPECT MORE
SPG
STORAGE PRODUCTS GROUP