# Structural Concepts° DELIVERING FRESH. ALWAYS.\*\*

GMDSV4R
 GMDSV5R
 GMDSV6R
 GMDSV6R
 GMDSV8R
 GMDSV8R
 GMDSV10R
 GMDSV10R
 GMDSV10R
 GMDSV12R
 GMDSV12R
 S1-5/8"H
 GMDSV12R
 GMDSV12R
 S1-5/8"H
 GMDSV12R
 S1-5/8"H
 GMDSV12R

## Included

- Remote DX refrigeration
- LED top & shelf lights
- One year parts & labor warranty
- One year parts & labor; 5 year compressor warranty
- Stainless steel rear exterior
- Vertical, UV bonded lift-up front glass w/o lock
- Warmest average product temperature of 40°F or less



Specify	Standard Features	Additional Options				
EXTERIOR COLOR	Laminate (stock colors)	Laminate (non-stock colors)				
		Powder coated (stock/non-stock colors)				
		Powder coated Silversan Black				
		Stainless steel				
INTERIOR COLOR	Powder coated Silversan Black	Stainless steel				
LOWER FRONT PANEL COLOR	Powder coated Silversan Black	Powder coated (stock/non-stock colors)				
		Stainless steel				
BASE SUPPORT	Rail system for shims (remote)					
BUMPER FRONT	• 1" Boston bumper (specify color)	1" Stainless steel plate rail bumper				
END PANELS	Full w/stainless steel mirror interior	Cutaway w/glass				
		None (specify per line-up)				
SCALE STAND	None	¹ • Scale stand w/ receptacle & CAT5 (specify location)				
		Scale stand w/ receptacle (specify location)				
PRICE TAG MOLDING	• None	1" Price tag molding (black or silver)				
		Universal price tag molding (clear w/ open top)				
REAR DOORS	Clear glass rear sliding doors	Reflective glass rear sliding doors				
SHELVING	• 16" Solid shelf	• 14" & 16" Solid shelving				
		• 14" & 20" Solid shelving				
LIGHTS	LED 3500K w/ frosted lens	LED 4000K w/ frosted lens				
		• LED nose light				
ELECTRICAL CONNECTION	Electrical leads (remote)					
REFRIGERATION	• Remote DX refrigeration	<sup>2</sup> • Remote w/thermostat, solenoid & TXV				
SENSOR	• None	CPC discharge air sensor (remote)				
MISCELLANEOUS		Front glass lock				
		Rear door lock				
ACCESSORIES		Angled display steps (n/a w/shelf)				
		Drain strainer				
		Rear wrapping board, white Sanalite®				
	OLINIA A Budinantatatatata	Out the Nation of Community of the Community of				

Std Notes: 1 - Read important notes for remote options


Option Notes: 1 - Separate circuit required

2 - Read important notes for remote options

# Structural Concepts

DELIVERING FRESH. ALWAYS.™


Intend	ted Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise	Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.								
Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F								
1	Unpackaged refrigerated products	38-40								



# GMDSV10R, GMDSV12R L2 GMDSV10R, GMDSV12R L2 TOE KICK TOE KICK

CASE FRONT GMDSV8R, GMDSV10R, GMDSV12R

## SIDE VIEW



NOTE: ALL DIMENSIONS APPROXIMATE

GMDSV8R L2

ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).

LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3/4" OR 11/2" PVC TUBE).

REFRIGERATION LINE CONNECTION.

REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

SELF-CONTAINED CASE SERVICE ACCESS AREA.

DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications																
Model	L"	L1"	L2"	System Circu	Phs	Freq	Amps	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt		
GMDSV4R	48.75	51.00	3.50	Remote (DX)	Circuit #1	110-120	1	60	1.70	71	2+G	Leads Multiple	20.00	1296	1200	
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	1.70	71	2+G	Leads Multiple	30.00	1296	1200	
				Remote (R744 TRANSCRIT	Circuit #1	110-120	1	60	1.70	71	2+G	Leads Multiple		1296	1200	
GMDSV5R	60.63	62.88	3.50	Remote (DX)	Circuit #1	110-120	1	60	2.63	90	2+G	Leads Multiple	20.00	1706	1580	1,150
GMDSV6R	73.13	75.38	8 3.50	Remote (DX)	Circuit #1	110-120	1	60	2.29	99	2+G	Leads Multiple	20.00	2030	1880	1,250
				Remote (R744 TRANSCRIT	Circuit #1	110-120	1	60	2.29	99	2+G	Leads Multiple		2030	1880	
GMDSV8R	97.50	99.75	3.50	Remote (DX)	Circuit #1	110-120	1	60	3.08	173	2+G	Leads Multiple	20.00	2722	2520	1,575
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	3.96	424	2+G	Leads Multiple	20.00	2722	2520	
				Remote (R744 TRANSCRIT	Circuit #1	110-120	1	60	3.76	149	2+G	Leads Multiple		2722	2520	
GMDSV10R	121.13	123.38	40.50	Remote (DX)	Circuit #1	110-120	1	60	6.05	576	2+G	Leads Multiple	20.00	2916	2700	1,600
					Circuit #1	110-120	1	60	6.05	576	2+G	Leads Multiple	20.00	2916	2700	
				Remote (R744 TRANSCRIT	Circuit #1	110-120	1	60	6.05	576	2+G	Leads Multiple		2916	2700	
GMDSV12R	146.25	148.50	45.25	Remote (DX)	Circuit #1	110-120	1	60	4.62	540	2+G	Leads Multiple	20.00	3672	3400	1,750
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	4.62	540	2+G	Leads Multiple	20.00	3672	3400	
				Remote (R744 TRANSCRIT	Circuit #1	110-120	1	60	4.62	540	2+G	Leads Multiple		3672	3400	

\*\*\* Does not include electric defrost on freezer models.

Regulatory Approvals:

All Models

Accordance with AHRI Std 1200

ETL Listed to UL 471

ETL Listed to CAN/CSA 22.2 No. 120

ETL Sanitation to NSF/ANSI 7



1 1/8" TYP

4 5/8" GMDSV8R = 24 3/8"

GMDSV10R = 30 1/4' GMDSV12R = 36 1/2'

In Accordance with
AHRI Std 1200

DOE 2017 Energy Efficiency

### **Important Notes:**

- 1) REMOTE REFRIGERATION NOTE: Condensing unit not included, floor drain required.
- 2) Units must be shimmed during installation to ensure the unit is level and plumb.
- 3) Compressor air rear intake, front discharge. Toe kick cannot be blocked.
- 4) Condensate pan with self-contained refrig. only.
- 5) Remote doesn't incl Conds unit. Floor drain reqd.
- 6) Remote only available w/rail base w/shims.

▲ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.