BACK BAR EQUIPMENT

Model: BB69NGD

Natural Refrigerant R-290 Model

69" Back Bar Display Cooler with Hinged Glass Doors

Textured baked black enamel finish exterior, stainless steel countertop, interior back and side panels with reinforced stainless steel floor.



Options and Accessories

(upcharge and lead times may apply)

| Additional epoxy coated shelves | Food storage rated stainless steel interior (NSF-7) |
|---------------------------------|---|
| Stainless steel shelves | Casters or legs |
| Wine rack | Compressor right (standard on left) |
| Riser base* | |

Consult factory for other model configurations, options and accessories.

* Adding a Riser Base increases overall height 2"



Model Specified:

Location:

Item No: Quantity:

AIA #: SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance rated front breathing refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Automatic, hot gas condensate evaporator

Extra large, balanced evaporator coil

CABINET ARCHITECTURE

High density, non-CFC polyurethane foamed-in-place insulation

Front, rear and side venting louvered grills

Triple pane, tempered low emissivity hinged glass doors

Magnetic snap in door gaskets

Cylinder keyed security lock in each door

Stainless steel reinforced threshold

MODEL FEATURES

Low profile cabinet design

Electronic control, off cycle defrost

LED interior lighting

Easily accessible and serviceable slide-out condensing unit

¹ R-290 refrigerant meets all federal and state regulatory requirements.





APPROVAL:

Model Specifications

| DIMENSIONAL DATA | |
|--|------------------------------|
| Net Capacity (cubic feet) | 26 (736 l) |
| Width, Overall (inches) | 69 (1753 mm) |
| Depth, Overall (inches) (including handles & bumpers) | 29 ³ ⁄16 (741 mm) |
| Depth, Body Only (inches) (less doors) | 25 (635 mm) |
| Height, Overall (inches) | 34 ¾ (883 mm) |
| Bottle/Can capacity (12 oz) | 86 (per shelf) |
| Number of Doors | 2 |
| Number of Shelves | 4 |

REFRIGERANT DATA

| Condensing Unit Size (H.P.) | 1/4 |
|-----------------------------|------|
| Capacity (BTU per hour)* | 1930 |

ELECTRICAL DATA

| Voltage (International) | 115/60/1 (220/50/1) |
|---|---------------------|
| Feed Wires (including ground) | 3 |
| Total Amps (International) | 3.7 (3.4) |
| 10 ft. Cord/Plug [attached] (International) | Yes (No) |

SHIPPING DATA

| Weight (pounds) | 400 (182 kg) |
|--------------------------|--------------|
| Height - Crated (inches) | 46 (1168 mm) |
| Width - Crated (inches) | 78 (1981 mm) |
| Depth - Crated (inches) | 42 (1067 mm) |

 * Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





IMPORTANT NOTE: Models are completely front breathing and take in and exhaust air through the front grill. For proper operation, the area in front of the cabinet must not be obstructed in any way. A clearance of 1" on the back and 3" on the sides is recommended.