



Stem Caster
without brake



Stem Caster
with brake


SPG Stem Casters

Model No.	Type	Swivel/Rigid	Material	Dia. (In.)	Face (In.)	Capacity (Lbs.)	Fits	Unit	Brakes	Weight (Lbs.) (Kg.)
CP5PR	Expandable, Stem	Swivel	Resilient Rubber	3	1	150	AMCO. ISS, ISS Contender	Ea.	NA	2 1
CM3MB	Expandable, Stem	Swivel	Resilient Rubber	3	1	150	AMCO. ISS, ISS Contender	Ea.	✓	2 1
CM5M	Expandable, Stem	Swivel	Resilient Rubber	5	1	200	AMCO. ISS, ISS Contender	Ea.	NA	2 1
CM5MB	Expandable, Stem	Swivel	Resilient Rubber	5	1	200	AMCO. ISS, ISS Contender	Ea.	✓	2 1
CM5P	Expandable, Stem	Swivel	Polyurethane	5	1	300	AMCO. ISS, ISS Contender	Ea.	NA	2 1
CM5PB	Expandable, Stem	Swivel	Polyurethane	5	1	300	AMCO. ISS, ISS Contender	Ea.	✓	2 1
AC7B	Stem	Swivel/Rigid	Polyurethane	5	1	250	AMCO	Ea.	✓	3 1
AC8RS	Stem	Swivel	Polyurethane	5	1	250	AMCO	Ea.	NA	3 1
IMPCAS5	Threaded Stem	Swivel	Polyurethane	5	1	250/Set	ISS Contender	Set(4)	✓*	6 3
4K1196	Expandable Stem for 1" Tube	Swivel	Polyurethane	5	1	—	Kelmax	Ea.	NA	2 1
4K0307	Square Stem	Swivel	Polyurethane	5	1.5	—	Kelmax	Ea.	NA	2 1
TAC-1-4	Stem	Swivel	Polyurethane	5	1	250	Universal	Set(4)	✓*	11 5
TAC-2-6	Stem	Swivel	Polyurethane	5	1	250	Universal	Set(6)	✓*	14 6

*Includes 2 brakes in the set

Donut Bumpers

Model No.	Width (In.)	Description
ADONUT	5	Revolving
DONUT2	3½	Non-Revolving



Caster Channels

- Required on all round stem rigid casters to maintain aligned position of casters
- Order one caster channel for each pair of rigid casters
- Select caster channel length based on shelf width



Plating Plus™ Model No.	Fits Shelf Width (In.)	W x L (In.)	(mm.)	Weight (Lbs.) (Kg.)
CC18C	18	2 x 19	57 x 476	1 1
CC21C	21	2 x 22	57 x 553	1.5 1
CC24C	24	2 x 25	57 x 629	2 1