DINEXPRESS COLD FOOD COUNTERS



Cold Food Counters

- Excellent for serving chilled fruit, drinks, salads, and desserts
- Available with 2 to 6 wells
- Counters come standard with heavy-duty
 5" casters (two locking) and with stainless steel base-skirting available
- Stainless or custom drop down shelves and tray slides available for all configurations
- Electric refrigerated and ice well units available
- Feature 5" or 9 7/16" deep wells (NSF7)
- Stainless sneeze guards
- Cold Storage Base available
- Under-shelf options
- Most units are NSF listed (see product chart for details)

Prod No	Description	LxDxH	Pack
Refrigerated F	Food Counters with Extra Deep Wells - 120 Volts / Single Phase / 7	7 Amps (NSF7)	
DXP2BCM ❖	Cold Food Counter - 2 Well (9.44" Deep Wells)	35" x 30" x 36"	1 ea
DXP3BCM ❖	Cold Food Counter - 3 Well (9.44" Deep Wells)	49" x 30" x 36"	1 ea
DXPBCM ❖	Cold Food Counter - 4 Well (9.44" Deep Wells)	63" x 30" x 36"	1 ea
DXP5BCM ❖	Cold Food Counter - 5 Well (9.44" Deep Wells)	77" x 30" x 36"	1 ea
DXP6BCM ❖	Cold Food Counter - 6 Well (9.44" Deep Wells)	91" x 30" x 36"	1 ea
Refrigerated F	Food Counters with 5" Deep Wells - 120 Volts / Single Phase / 7 A	mps	
DXP2CM △	Cold Food Counter - 2 Well (5" Deep Wells)	35" x 30" x 36"	1 ea
DXP3CM △	Cold Food Counter - 3 Well (5" Deep Wells)	49" x 30" x 36"	1 ea
DXP4CM △	Cold Food Counter - 4 Well (5" Deep Wells)	63" x 30" x 36"	1 ea
DXP5CM △	Cold Food Counter - 5 Well (5" Deep Wells)	77" x 30" x 36"	1 ea
DXP6CM △	Cold Food Counter - 6 Well (5" Deep Wells)	91" x 30" x 36"	1 ea
Cold Food Cou	unters (Ice Bath)		
DXP2CI △	Cold Food Counter - 2 Ice Well	35" x 30" x 36"	1 ea
DXP3CI △	Cold Food Counter - 3 Ice Well	49" x 30" x 36"	1 ea
DXP4CI △	Cold Food Counter - 4 Ice Well	63" x 30" x 36"	1 ea
DXP5CI △	Cold Food Counter - 5 Ice Well	77" x 30" x 36"	1 ea
DXP6CI △	Cold Food Counter - 6 Ice Well	91" x 30" x 36"	1 ea

 $NSF\ 7\ listed\ products\ are\ designated\ with\ a\ \diamond.$ Dinex NSF listed products are designated with a Δ and may be prefixed with an N.



Product Specifications Can Be Customized.