

# DISPLAY REFRIGERATOR

## Model: 2RSNSGD

Natural Refrigerant R-290 Model

### 2-Section Display Reach-In Refrigerator with Sliding Glass Doors Shallow Depth

**2RSNSGD** - Stainless steel front, aluminum end panels and interior  
**2RSNSASGD** - Stainless steel exterior, aluminum interior  
**2RSNSSGD** - Stainless steel exterior and interior  
Designed to maintain NSF-7 temperatures in 100°F ambient.



## Options and Accessories

(upcharge and lead times may apply)

Stainless steel case back	Adjustable legs
Additional epoxy coated steel shelves	Expansion valve
Chrome or stainless steel shelves	Special electrical requirements (consult factory)
Heavy duty pilaster strips	Wine rack

Consult factory for other model configurations, options and accessories.

**Continental**<sup>®</sup>  
Refrigerator



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

## Standard Model Features

### REFRIGERATION SYSTEM

Self contained, performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Automatic, electric condensate evaporator

### CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Double-pane, tempered sliding glass doors

Snap in door wiper

Self-closing doors

Heavy duty, epoxy coated steel shelves

5" casters

### MODEL FEATURES

LED interior lighting

Electronic control, off cycle defrost

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

Net Capacity (cubic feet)	32 (813 l)
Width, Overall (inches)	52 (1321 mm)
Depth, Overall (inches) (including grill)	27 <sup>7</sup> / <sub>8</sub> (708 mm)
Depth (inches) (less grill)	25 <sup>7</sup> / <sub>8</sub> (657 mm)
Clear Door Width (inches)	17 <sup>3</sup> / <sub>4</sub> (451 mm)
Clear Door Height (inches)	54 <sup>3</sup> / <sub>4</sub> (1391 mm)
Height, Overall (inches) (including 5" casters)	82 <sup>1</sup> / <sub>4</sub> (2089 mm)
Number of Doors	2
Number of Shelves	8
Shelf Area (square feet)	40.8 (3.8 sq m)

### REFRIGERANT DATA

Condensing Unit Size (H.P.)	<sup>1</sup> / <sub>3</sub>
R-290 Refrigerant Charge (oz)	4.6
Capacity (BTU per hour)*	2540

### ELECTRICAL DATA

Voltage (International)	115/60/1 (220/50/1)
Feed Wires (including ground)	3
Total Amps (International)	4.6 (2.3)
10 ft. Cord/Plug [attached] (International)	Yes (No)

### SHIPPING DATA



Height - Crated (inches)	85 <sup>1</sup> / <sub>2</sub> (2172 mm)
Width - Crated (inches)	64 (1626 mm)
Depth - Crated (inches)	42 (1067 mm)
Volume - Crated (cubic feet)	133 (3766 cu l)
Weight Std - Crated (pounds)	420 (190 kg)
Weight SS - Crated (pounds)	505 (229 kg)

\* Rating @ +25°F evaporator, 90°F ambient  
 Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)

## Model Plan Views



**IMPORTANT NOTE:** If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides and rear.

**Continental**  
 Refrigerator

Toll-Free: 800-523-7138  
 Phone: 215-244-1400  
 Fax: 215-244-9579

539 Dunksferry Road  
 Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.

