

Cadco HALF SIZE HEAVY DUTY MANUAL



Model: XAF-113

Half Size, 3 Shelf, Manual Control, 120v (With Humidity) Unit Dimensions (W" x H" x D"): 23 5/8 x 16 7/8 x 28 1/8 Cavity Size (W" x H" x D"): 19 1/2 x 10 x 151/2; 1.75 cft.

One fan. NEMA 5-15P plug

Volts: 120 Watts: 1450 Amps: 12

Shipping Weight (lbs.): 120* Stands available: OST-34A-C, OST-34A-Cs.

Heavy-Duty 2-Oven Stand also available: OV-HDS

Stackable with CXC651 Stacking Kit

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube
XAF-113	Stainless	120	1450	12	w:235/8", h:167/8", d:281/8"	74 lbs.	120* lbs.	w:42", h:217/8", d:48"*	25.53



Model: XAF-133

Half Size, 4 Shelf, Manual Control, 220v (With Humidity) Unit Dimensions (W" x H" x D"): 23 5/8 x 20 x 28 1/8 Cavity Size (W" x H" x D"): 19 1/2 x 13 x 15 1/2; 2.27 cft.

One fan. NEMA 6-20P plug)

Volts: 208-240 Watts: 2700 Amps: 20 NSF

Shipping Weight (lbs.): 125*

Stands available: OST-34A-C, OST-34A-CS. Heavy-Duty 2-Oven Stand also available: OV-HDS Stackable with CXC651 Stacking Kit

	Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube
ſ	XAF-133	Stainless	208-240	2700	20	w:235/8", h:20", d:281/8"	80 lbs.	125* lbs.	w:42", h:25", d:48"*	29.17*

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

- 3" between shelves
- "Cool-touch" double wall glass door
- Oven cavity is wrapped in high "R" value insulation
- 60 minute timer or continuous on
- Timer beeps at end of cycle
- Heat settings from 175°-500° F
- Heavy duty stainless steel construction
- High temperature motor bearings
- Heavy duty door & hinge construction
- LED light in door
- Dimensions are designed to accommodate modular stacking for customized configuration
- 2 year Limited Warranty (one year On-site service & parts, 2nd year parts only)**
- 90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- Freight class 200 NOTE: This model must ship by truck, not UPS



