



IFSCB250

Filter System with Drain Station

MODEL NUMBERS

IFSCB150 IFSCB450 IFSCB175 IFSCB475 IFSCB250 IFSCB550 IFSCB275 IFSCB575 IFSCB350 IFSCB650 IFSCB375 IFSCB675



With Hands-free Filter Connection System

FILTER PACKAGE CHOICES

- Up to six fryers can be batteried into one fryer / filter system.
- Available for 50 and 75 lb. (27 and 41 Liters) oil capacity fryers.
- Available in Snap Action Thermostats, Electronic Thermostats or Computer Controls.

LOCATED UNDER FRYERS

- Filter location under fryers saves valuable space.
- · Internally plumbed oil drain and return line.

UNIQUE FILTER PAN DESIGN

- Filter pan is designed for maximum oil return.
- Stainless steel construction is easy to clean and has a professional look.
- · Positive-latching filter paper holder holds paper in place for optimal filtration.
- Quick disconnect connection offers quick and safe connection of the filtered oil back into the frypots.
- All oil drain and return lines are internally plumbed for convenience and safety.

ROLLER-PUMP

- 5.5 GPM pump with a 1/3 HP motor speeds up filtering process
- Can pump oil into a disposal vat up to 20 feet away.
- · Reclamation system

DRAIN STATION

- Includes a matching stainless steel cabinet with a food warmer and dump pan.
- Cabinet may be located anywhere within the fryer battery.
- · Cabinet is a convenient storage area when located at the end of the battery.

EXTERIOR FEATURES

- Continuous cabinet provides a professional look.
- 5" (127 mm) deep continuous stainless steel front landing ledge.
- Stainless steel precision welded frypot. Includes casters, joiner strips and filter starter kit.
- Rear gas manifold with one point gas connection.





Touch Screen Digital Controls Now Available!






TUBE FIRED SIDE CAR FRYER FILTER SYSTEMS







| MODEL | OIL CAPACITY | WIDTH | FRYERS | SHIP WEIGHT KG | SHIP WEIGHT LBS |
|----------|----------------|--------------------|--------|----------------------|-----------------------|
| IFSCB150 | 50 LBS. (41 L) | 31" (787 MM) | 1 | 196 | 433 |
| IFSCB250 | 50 LBS. (41 L) | 46-1/2" (1181 MM) | 2 | 311 | 686 |
| IFSCB350 | 50 LBS. (41 L) | 62" (1575 MM) | 3 | 426 | 939 |
| IFSCB450 | 50 LBS. (41 L) | 77-1/2" (1969 MM) | 4 | 541 | 1192 |
| IFSCB550 | 50 LBS. (41 L) | 93" (2362 MM) | 5 | 655 | 1445 |
| IFSCB650 | 50 LBS. (41 L) | 108-1/2" (2756 MM) | 6 | 770 | 1698 |
| IFSCB175 | 75 LBS. (51 L) | 39" (911 MM) | 1 | 204 | 450 |
| IFSCB275 | 75 LBS. (51 L) | 58-1/2" (1486 MM) | 2 | 327 | 720 |
| IFSCB375 | 75 LBS. (51 L) | 78" (1981 MM) | 3 | 449 | 990 |
| IFSCB475 | 75 LBS. (51 L) | 97-1/2" (2477 MM) | 4 | 572 | 1260 |
| IFSCB575 | 75 LBS. (51 L) | 117" (2972 MM) | 5 | 694 | 1530 |
| IFSCB675 | 75 LBS. (51 L) | 136-1/2" (3467 MM) | 6 | 816 | 1800 |

| FILTER ELECTRICAL REQUIREMENT | | | | | | | |
|-------------------------------|-------|-------|----------|--|--|--|--|
| VOLTS | PHASE | HERTZ | AMPS | | | | |
| 115 V | 1 | 60 | 6.8 AMPS | | | | |

6ft. (1829 mm) power cord with 3 prong plug provided

CLEARANCE

For use only on non-combustible floors with legs or casters. Provide 0" clearance from non-combustible surfaces and 6" (152 mm) from combustible surfaces.

OPTIONS AND ACCESSORIES

- Automatic basket lifts with computerized controls
- Manual controlled basket lifts
- Gas shut off valve, 3/4" N.P.T.Stainless steel tank cover
- Stainless steel tank cover
 Stainless steel side drain shelf
- Stainless steel side drain shell
 Stainless steel side splash, 6"
- Filter paper 40# thickness, 20 microns, 100 sheets per box



| MODEL | DIMENSIONS | CRATED DIMENSIONS | MODEL | DIMENSIONS | CRATED DIMENSIONS |
|----------|--|---|----------|--|---|
| IFSCB150 | 31" W X 33-1/4" D X 51-1/2" H (787 X 845 X 1308 MM) | 32-1/2" W X 38" D X 40" H (826 X 965 X 1016 MM) | IFSCB175 | 39" W X 40-1/2" D X 45-3/4" H (911 X 1029 X 1162 MM) | 40-1/2" W X 43" D X 49-1/2" H (1029 X 1092 X 1257 MM) |
| IFSCB250 | 46-1/2" W X 33-1/4" D X 51-1/2" H (1181 X 845 X 1308 MM) | 48" W X 38" D X 40" H (1219 X 965 X 1016 MM) | IFSCB275 | 58-1/2" W X 40-1/2" D X 45-3/4" H (1486 X 1029 X 1162 MM) | 60" W X 43" D X 49-1/2" H (1524 X 1092 X 1257 MM)Z |
| IFSCB350 | 62" W X 33-1/4" D X 51-1/2" H (1575 X 845 X 1308 MM) | 63-1/2" W X 38" D X 40" H (1613 X 965 X 1016 MM) | IFSCB375 | 78" W X 40-1/2" D X 45-3/4" H (1981 X 1029 X 1162 MM) | 79-1/2" W X 43" D X 49-1/2" H (2019 X 1092 X 1257 MM) |
| IFSCB450 | 77-1/2" W X 33-1/4" D X 51-1/2" H (1969 X 845 X 1308 MM) | 79" W X 38" D X 40" H (2007 X 965 X 1016 MM) | IFSCB475 | 97-1/2" W X 40-1/2" D X 45-3/4" H (2477 X 1029 X 1162 MM) | 99" W X 43" D X 49-1/2" H (2515 X 1092 X 1257 MM) |
| IFSCB550 | 93" W X 33-1/4" D X 51-1/2" H (2362 X 845 X 1308 MM) | 94-1/2" W X 38" D X 40" H (2400 X 965 X 1016 MM) | IFSCB575 | 117" W X 40-1/2" D X 45-3/4" H (2972 X 1029 X 1162 MM) | 118-1/2" W X 43" D X 49-1/2" H (3010 X 1092 X 1257 MM) |
| IFSCB650 | 108-1/2" W X 33-1/4" D X 51-1/2" H (2756 X 845 X 1308 MM) | 110" W X 38" D X 40" H (2794 X 965 X 1016 MM) | IFSCB675 | 136-1/2" W X 40-1/2"D X 45-3/4" H (3467 X 1029 X 1162 MM) | 138" W X 43" D X 49-1/2" H (3505 X 1092 X 1257 MM |

