



# WLF46B

Worktop 46" Side Mount  
Freezer with One Door

STEELHEART™



WLF46B  
06/27/25  
Item # 13729

## W x D x H

46 x 33.25" x 40.25"\*

Work Height 36"\*

\*with 6" casters



## Dimensions / Capacity

**Interior Storage Capacity** (CF) (AHAM)

**Overall Width x Depth** (including 1" bumper)

**Height** (including 6" casters)

**Door Opening Width x Height**

**Depth with Door Open at 90°** (including 1" bumper)

**Adjustable Shelves**

**Shelf Dimensions** (W x D)

**Crated Weight**

**Crated Length x Width x Height**

## One-Section WLF46B

11.78 ft³

46" x 33.25"

40.25"

25.5" x 23"

60.5"

2

28.75" x 25.5"

278 lbs.

48.75" x 34.75" x 40"

## Electrical / Refrigeration

**Voltage**

**HACR Breaker**

**Electrical Connection** (NEMA)

**Voltage Range**

**Ambient Temp. Range**

**Control Setpoint Range**

**Recommended Setpoint**

**Amperage**

**Energy Consumption** (kWh/day) @ASHRAE

**Heat Rejection** (BTU/Hr.) @NSF

**Approx. Nominal Compres.** BTU/HR (HP)

**Refrigerant / Charge Amount** (oz)

## One-Section WLF46B

115/60/1

15.0 Amps

5-15P ⚡

104-126

45° to 100°F

-10° to 10°F

2°F

4

3.36

645

2431 (1/3+HP)

R290 (2.6 oz)

## Options

☐ 2" Casters (HS-5037, set of 4)

☐ 4" Casters (HS-5035, set of 4)

☐ Foot pedal kit (HS-5555, Lft hinge)

☐ Foot pedal kit (HS-5556, Rt hinge)

☐ Pan slide rack (HS-5514)

☐ Overshelves (HS-5229 single)

☐ Overshelves (HS-5228 double)

☐ Addtl. Epoxy Shelves (HS-5152, 1pk)

☐ Addtl. Stainless Shelves (HS-5154, 1pk)



Seven year warranty  
on labor, parts, and  
compressor. Valid in  
United States, Canada,  
Puerto Rico and U.S.  
Territories.

For more information, please visit  
[hoshizakiamerica.com/support/warranty/](https://hoshizakiamerica.com/support/warranty/)

Item #: \_\_\_\_\_

Project: \_\_\_\_\_

Qty: \_\_\_\_\_

AIA#: \_\_\_\_\_

## Features

► Front breathing air flow design allows for 1" of rear wall clearance

► Stainless steel exterior front, sides, and top with stainless steel interior

► Engineered to maintain NSF-7 temperatures in 100°F ambient

• Environmentally friendly R290 hydrocarbon refrigerant

• Cabinet and doors are insulated with 2" CFC free, foamed in place polyurethane

• Exclusive "stepped" door design to protect door gasket

• Spring assisted self-closing doors with stay open feature

• Extruded aluminum flush mount door handle

• Field reversible doors with magnetic snap-in gaskets

• Magnetic door gaskets are easily removable for cleaning

• Removable air filter for easy cleaning

• Hot gas condensate removal

• E-coated evaporator coil

• Digital temperature display

• Two epoxy coated shelves is standard

• Shelves hold a full sized sheet pan & 120 lbs. capacity

• Anodized aluminum shelf supports adjustable in 1/2" increments

• Standard with 6" casters (three with brakes)

• 10 ft. cord and plug

If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle

Hoshizaki reserves the right to change specifications without notice.




# WLF46B

## Worktop 46" Side Mount Freezer with One Door




WLF46B  
06/27/25  
Item # 13729


FRONT VIEW



SIDE VIEW



PLAN VIEW



### Cabinet Construction

The exterior cabinet top, front, and sides, are constructed of high quality stainless steel. The exterior back and bottom are constructed of coated steel. The cabinet interior features stainless steel back, sides, top and floor. Two heavy duty epoxy coated shelves is standard. Mounted on anodized aluminum pilasters the shelves are adjustable in 1/2" increments. Cabinet walls are insulated with 2" CFC free, foamed in place polyurethane. 6" polyolefin, stem casters (three with brakes) are standard.

### Door Construction

Doors are constructed of high grade stainless steel exterior with an ABS interior liner and are insulated with 2" CFC free, foamed in place polyurethane. Hoshizaki's exclusive "stepped" design protects the gasket while product is removed from the cabinet. Doors are provided with a one piece, extruded aluminum, flush mount handle. Spring assisted self-closing doors are equipped with a stay open feature past 90 degrees. Snap-in magnetic door gaskets are durable and easily removed for cleaning. Field reversible door hinging is standard.

### Refrigeration System

The high efficiency refrigeration system is self-contained with an E-coated evaporator for extended life. Condensate removal is accomplished with an energy efficient non-electric evaporation system. A capillary tube controls the flow of environmentally friendly R290 refrigerant through the evaporator. Unit uses a heated, time initiated defrost to eliminate any ice on the evaporator coil. 115 volt units are equipped with a ten foot cord and plug (20.0 amps or less).