

THERMOCOUPLE PROBES

High quality thermocouple thermometers should be coupled with the most in the foodservice industry and are well suited for numerous tasks. Each probe resistant cables. Probes are designed and built to the highest standards allowing

Used to measure insertion and immersion temperatures of food products

- ▶ **MOST EXTENSIVE PROBE LINE IN THE INDUSTRY**
- ▶ **ALL PROBES MANUFACTURED IN AN ISO 9001:2008 FACILITY**



50316-K
Flat-tipped immersion probe that can be used to take surface temperatures.



	50334-K	50335-K	50336-K	
	DuraNeedle - Straight Cable	Needle Probe w/ Coil Cable	DuraNeedle - Coil Cable	
Temperature Range:	-100° to 500°F (-73° to 260°C)	-40° to 500°F (-40° to 260)	-40° to 500°F (-40° to 260)	
Max Tip Temperature:	500°F (260°C)	500°F (260°C)	500°F (260°C)	
Max Cable Temperature:	400°F (205°C)	176°F (80°C)	176°F (80°C)	
Response Time (in liquid):	1 second	4 seconds	2 seconds	
Shaft Length:	4" (102 mm)	4.5" (114 mm) 8" and 10" Available	6" (152 mm)	
Shaft Tip Diameter:	0.085" (2.2 mm)	0.125" (3.2 mm)	0.085" (2.2 mm)	
Cable Length Max Extended:	34" (864 mm) Fluoroelastomer Jacket	48" (1.2 m) Polyurethane Jacket	48" (1.2 m) Polyurethane Jacket	
Weight:	2 oz (57 g)	2 oz (57 g)	2 oz (57 g)	
Warranty:	1 Year	1 Year	1 Year	