

PROJECT:		
ITEM #		OTY:
MODEL#		
AIA#	SIS #	
MA II	. 010 //	

UNDERCOUNTER REFRIGERATOR WITH DRAWERS

VURD93HC-2



EXCLUSIVE WARRANTY

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)











CABINET CONSTRUCTION

- · Stainless Steel Exterior (galvanized back and bottom)
- · Aluminum Interior
- · Stainless Steel 20 Gauge Door/Drawers
- · One Piece, Snap-In Magnetic Door/Drawer Gaskets
- · 6" Casters Two With Brakes
- · 8' Cord And Plug (see electrical data for details)

FEATURES

- · Full Electronic Control
- · Stay-Open Door Feature For Easy Product Loading
- · Heavy-Duty Spring Loaded Cartridge Hinges
- · Heavy-Duty Pan Supports Provided
- Drawers Accommodate 6" Deep Full Size Food Service Pans In Both Upper And Lower Drawers (pans not included)
- · Telescoping Drawer Slides With Locking Mechanism
- · Low Profile Horizontal Door/Drawer Handles
- · Epoxy Coated Shelves (2 per section)

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Side Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- **Epoxy Coated Evaporator Coil**
- Refrigerator Capable Of Maintaining Product Temperature 36°F To 38°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- · Stainless Steel Interior
- · Stainless Steel Back
- Door/Drawer Locks
- · Cutting Board

- Additional Shelves
- · Shelf Clips (set of 4)
- · Door Swing Orientation (at time of order)
- · 6" Legs Or 6" Seismic Legs
- · Casters: 3", Roller Kit, Low Profile
- · Correctional Package
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)


3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168


Rev 7/19/24 Printed in U.S.A. APPROVAL: _ DATE: _




VURD93HC-2










Drawer Configurations



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

3" Bottom & 2" Rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	29.7	Cabinet Voltage	115/60/1	Height	38"
Width, Overall (in.)	93 1/8"	Total Amperes	5.0	Width	96"
Depth, Overall (with handle)	33 7/8"	NEMA Plug (8' cord)	5-15P	Depth	42"
Height Overall (6" casters)	34 1/2"	REFRIGERATION DATA		Crated Weight	473 lbs
Depth, Drawer Open 90°	56 3/4"	Condensing Unit Size, HP	1/3	*NOTE: Remote units are field wired and comes with 6' legs. Refrigerant must be specified at time of order.	
Door Opening (in.)	215/8" x 23 5/8"	Refrigerant*	R-290		
Drawer Openings (in.)	21 5/8" x 10 3/8"	Capacity (BTU/HR) (100°F/20°F)	2630		
No. Of Doors/Shelves/Drawers	2/4/2	Heat Rejection (BTU/HR)	3945		
		Charge (lbs/grams/ounces)	0.3086 / 140 / 4.94		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 7/19/24 Printed in U.S.A.

