

www.glastender.com





4004503 Conforms to NSF/ANSI STD 7

Intertek

and UL STD 471 Certified to CSA STD C22.2 No. 120



Capable of storing specialty cocktail ice

#### AIA# Project: Item #: Qty: SIS# Model #:

# Frosters, One Zone, Side Serviced, Bar Profile

F1SB

F1SB24, F1SB28, F1SB36, F1SB44, F1SB48



## Configurable Options

### **Refrigeration Compartment** Location:

· Left or Right

### **Refrigeration Compartment** Cover Finish:

- · Black vinyl-clad
- · Stainless steel
- Jeweled stainless

### Door Style & Finish (specify per door section):

- · Black vinyl-clad
- · Stainless steel
- · Jeweled stainless
- Laminated
- Unlaminated
- · Glass, black vinyl-clad
- · Glass, stainless steel
- · Glass, jeweled stainless
- · Glass, laminated

## Drawer Style & Finish:

- · Black vinyl-clad
- Stainless steel
- · Jeweled stainless
- Laminated
- Unlaminated

#### **Door Hinge Location**

Left or Right

### **Door Handle:**

- Signature (drawers excluded)
- Pull-tab
- Tube

#### Top Style:

- · No finished top
- · Stainless top

## Left and Right Side Finish:

- · Black vinyl-clad
- · Stainless steel

### **Back Finish:**

- · Galvanized steel
- · Stainless steel

## **LED Lighting Style:**

- Bright white (7,000k)
- Warm white (3,500k)
- Amber (2,700k)
- Blue

### Standard Features

Self-contained

Intertek

EP 5016978

Energy Performance Verified / Rendement

Énergétique Vérifié

- Stainless steel interior
- Locking door(s)
- LED interior lighting
- Two defrost cycles
- Automatic condensate evaporator
- Heated cabinet front to minimize condensation
- · Three adjustable, coated-wire shelves

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444 www.glastender.com

Specifications subject to change without notice. For current specifications please visit our website.

Approval/Notes:

# Frosters - One Zone, Side Serviced, Bar Profile

## **Specifications**

		F1SB24	F1SB28	F1SB36	F1SB44	F1SB48		
Dimensions	Length	24"	28"	36"	44"	48"		
	Number of Sections	1	1	2	2	2		
	Door Opening	17.5"	20"	12"	16"	18"		
Electrical	Electrical Supply	120V, 1 phase, 60 Hz, dedicated 15A circuit required						
	Full Load Amps	5.0						
	Plug Type	8 foot NEMA 5-15P grounded cord and plug which exits the back of refrigeration compartment						
Refrigeration	Refrigerant	R290 refrigerant - 130 grams, 4.59 oz, 0.29 pounds						
	Compressor	Reciprocating, 1/3 HP, 1300 BTUH, 0.11 Tons						
	Heat Rejection	2048 BTUH						
Operating Range		12°F (-11°C) to 35°F (2°C)						
Plumbing		Automatic condensate evaporator. No drain connection required †						
Weight Bearing Capacity		Countertops and other accessories should not exceed 500 pounds per door						

#### **Materials**

- · Stainless steel parts include: exterior sub-top, interior, front of cabinet, hinges, hinge and lock brackets, and optional legs
- · Black vinyl-clad steel parts include: standard sides, doors and compressor cover
- · Galvanized steel parts include: back and bottom

### Refrigeration

- Fin & tube evaporator with forced air circulation
- Equipped with manual fast freeze mode that accelerates the freezing process and automatically reverts back to the normal operating mode



† Building conditions outside the guidelines of ASHRAE 55 and ASHRE 62.1 may need to be plumbed to a drain.

## Capacities

	F1SB24	F1SB28	F1SB36	F1SB44	F1SB48
10 oz. Mugs	132	160	223	299	339
6" High Pint Glasses	97	100	155	200	214

## Frosters - One Zone, Side Serviced, Bar Profile

## Drawings







