Pizza Prep Tables FPT Series

FPT-46 FPT-67 FPT-93



Item # _____

Standard Features

- Our pizza units are designed with durability and strength that you will not find in any other products in its class.
- All stainless steel interior and exterior construction for a clean & safe food environment. Coved corner floor to meet NSF requirements.
- Heavy duty stainless steel door with full length recessed door handles; interior instep design for added insulation and protection of door gasket.
- With innovative and eco-friendly technology, Fagor utilizes R-290
 Hydrocarbon designed to meet DOE's Energy Conservation
 standards with very low contribution to global warming (ODP-0)
 (GWP-3).
- Forced air design underneath the pans to keep products fresh and maintain temperature at 33° - 41°F in food pans and cabinet interior. Complies with NSF7 standards for food product safety.
- Insulated lid keeps pan temperature cold and minimizes condensation. Removable for easy cleaning.
- Side breathing refrigeration system for built-in applications.
- Standard with rail system which holds (2) shelves per door and rails that can also accommodate (2) 12" x 20" foodservice pans (pans sold separately).
- 19" full length removable and reversible white polyethylene cutting board.



FPT-46



FPT-67



FPT-93

Options & Accessories

- 6" adjustable legs (set of 4)
- Additional epoxy coated shelves with channels
- Universal tray slides (pair)
- 220 Voltss / 50 cycles / 1 phase















*Conforms to UL & NSF-7 standards

ples	Model	Doors	Top Pans	Shelves	Capacity Cu. Ft.	Amps	НР	Volts	Cabinet Dimensions W/D/H			Shipping (Wt. Cubes)	
	FPT-46	1	6	2	9.9	3.0	1/3	115	46"	32-1/2"	43-7/8"	328	63
zza	FPT-67	2	9	4	18.6	3.0	1/3	115	67-1/4"	32-1/2"	43-7/8"	450	73
Piz	FPT-93	3	12	6	26.5	3.0	1/3	115	93-1/8"	32-1/2"	43-7/8"	570	92

^{*} Depth does not include 1" bumper. ** Height does not include 5" casters (6" overall) or 6" optional legs. All specifications are subject to change without notice.

Pizza Prep Tables FPT Series



Specifications

Construction

Heavy duty stainless steel exterior top, front and sides. Galvanized back panel. Interior completely constructed of heavy duty stainless steel with coved corner floor. Aluminum split wall between the food pans and the interior cavity.

Doors: heavy duty stainless steel exterior and interior, in-step design with hinged solid doors and positive seal. Self closing mechanism and 120° stay open feature.

Door openings have a plastic breaker strips to retard condensate formation. Provided with magnetic door gaskets, removable without tools. Recessed full length handles.

Units come complete with a 2" Ecomate CFC. Free polyurethane insulation, foamed in place.

Refrigeration System

Self-contained capillary tube system using environmentally friendly (CFC Free) R-290 refrigerant. Side mounted compressor on right side for built-in applications. Evaporator coil is mounted to interior top panel encased in stainless steel. Large fan motor and fan blades for better air flow.

Refrigerators are designed to maintain temperatures between 33 °F to 38 °F in the interior cabinet and 41 °F in the top rail.

Features

19" wide removable and reversible cutting board, NSF approved white polyethylene, 1/2" deep. Stainless steel insulated top lid keeps pan contents colder. Durable, long lasting and removable for easy cleaning.

Comes standard with standard-1/3 size, clear polycarbonate, NSF approved 6" deep food pans.

Shelving


(2) Epoxy coated shelving per door with channel slides for supports. Adjustable in 2" increments per shelf.


Others


Unit is supplied standard with a 8' cord and plug (Nema 5-15p). Standard with 5" diameter casters, front two with brakes.


Warranty


3 year parts and labor warranty plus 2 additional year compressor warranty. (Continental U.S.A. & Canada only).














The manufacturer reserves the rights to modify materials and specifications without notice.