

Kelmax Cantilever Frames and Adjustable Shelves

- Tubular base dunnage shelf is standard, and easily removed without the use of tools for cleaning
- Up to 5 additional shelf positions — shelves can be added or removed without tools
- Available in two shelf depths: 20" and 24"
- Clearance between adjustable shelves is 10"
- Maximum load capacity per shelving unit is 2,800 lbs
- Frames and adjustable shelves sold separately

Kelmax Cantilever Frames

Model No.	(in.)	L x W x H (mm)	Weight (Lbs.)	(Kg)
20-In Deep Shelving Frame				
4H4201	36 x 20 x 72	914 x 508 x 1829	49	22
4H4366	48 x 20 x 72	1219 x 508 x 1829	55	25
4H4482	60 x 20 x 72	1524 x 508 x 1829	61	27
24-In Deep Shelving Frame				
4H4501	36 x 24 x 72	914 x 610 x 1829	64	29
4H2977	48 x 24 x 72	1219 x 610 x 1829	75	31
4H4500	60 x 24 x 72	1524 x 610 x 1829	86	39



Kelmax Cantilever Shelves

Channel Shelf Model No.	Tubular Shelf Model No.	Solid Shelf Model No.	(in.)	L x W (mm)	Weight (Lbs.)	(Kg)
20-in. Deep Shelves						
4H4202	4H4203	4H4450	36 x 20	914 x 508	10	4
4H4368	4H4439	4H4561	48 x 20	1219 x 508	12	5
4H5129	4H4568	4H4484	60 x 20	1524 x 508	14	6
24-in. Deep Shelves						
4H4713	4H4505	4H5132	36 x 24	914 x 610	11	5
4H2978	4H2979	4H4938	48 x 24	1219 x 610	13	6
4H4763	4H4504	4H5473	60 x 24	1524 x 610	15	7



SPG's foodservice products are all manufactured to meet NSF standards. For specific items, visit www.nsf.org

Kelmax Tubular Base Dunnage Shelf

Model No.	(in.)	L x W (mm)	Weight (Lbs.)	(Kg)
20-Inch Deep Shelves				
4H4400	36 x 20	914 x 508	10	4
4H4367	48 x 20	1219 x 508	12	5
4H4483	60 x 20	1524 x 508	14	6
24-Inch Deep Shelves				
4H4509	36 x 24	914 x 610	11	5
4H4432	48 x 24	1219 x 610	13	6
4H4508	60 x 24	1524 x 610	15	7

How To Order

1. Choose frame size
2. Choose tubular base dunnage shelf that matches the frame size
3. Choose type of shelf (channel, tubular or solid) and the shelf size
4. Specify the number of shelves