

Stadium Series Ice Bin

Stadium Series



KRS-24 shown

Model	Length (A)	Depth	Body Height (B)	Wgt. (lbs)
KRS-24	12"	24"	13-½"	72
KRS-24-10	12"	24"	16-½"	129
KRS-24DP-10	18"	24"	19-½"	138
KRS-30	18"	24"	13-½"	81
KRS-30-10	24"	24"	16-½"	143
KRS-30DP-10	24"	24"	19-½"	153
KRS-36	30"	24"	13-½"	91
KRS-36-10	30"	24"	16-½"	157
KRS-36DP-10	36"	29"	19-½"	167
KRS-42	36"	24"	13-½"	100
KRS-42-10	42"	24"	16-½"	167
KRS-42DP-10	42"	24"	19-½"	176
KRS-48	48"	24"	13-½"	110
KRS-48-10	48"	24"	16-½"	176
KRS-48DP-10	48"	24"	19-½"	186

Standard Features

- Additional 5" chase added to back of unit for easy access, install and serviceability
- Storage cabinets with doors come standard with locks
- Optional perforated insert available for drainboard top
- Optional middle shelf available

Specifications

Material	▪ Interior: 20 gauge stainless steel
	▪ Front Apron: 20 gauge stainless steel clad over 20 gauge galvanized steel
	▪ Backsplash: 20 gauge stainless steel
	▪ Back and Bottom: 20 gauge galvanized steel
Legs	▪ 1-5/8" tubular 16 gauge stainless steel with grey plastic bullet foot
Insulation	▪ Foamed-in-place polyurethane
Cold Plate	▪ Model numbers that end '-10' include high performance built-in 10-circuit post mix cold plate.
	▪ Plate is sealed into bottom of ice bin
	▪ Each circuit is 5/16" OD stainless steel tubing
	▪ Two full with remainder to be half circuits
Plumbing	▪ Bump and swedge fittings on ends
	▪ 1" IPS drain connection
	▪ Units with cold plates: 1/2" x 6" PVC tailpiece (1/2" -20 male threaded) included.
	▪ PVC tailpiece required to avoid condensation through metal to metal contact
Tubing Access (Cold Plate)	▪ 3/4" x 3-1/2" cutout in left side of backsplash

