Plate Casters for Commercial Equipment



5" Heavy-Duty Universal Square Plate Casters w/Brakes

- Grease-resistant, non-marking, polyurethane wheels with brakes
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- 500 lb (227 kg) capacity per wheel for heavy-duty applications
- Temp. range: 14°F to 212°F (-10°C to 100°C)

Item #	Description	Capacity per Caster	Case
FPCST5HD	Set of 4 - 5" (12.7 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes	500 lbs (226 kg)	4
FPCST5HD	Individual 5" (12.7 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes	500 lbs (226 kg)	4

2" Universal Low-Profile Plate Casters w/Brakes

- 2" (5.1 cm) wheels with brakes
- Adds 3" (7.6 cm) to overall height
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- 200 lb. (91 kg) capacity per wheel
- Temp. range: 14°F to 212°F (-10°C to 100°C)

Item #	Description	Capacity per Caster	Case
FPCS352	Set of 4 - 2" (5.1 cm) Universal Plate Casters w/Brakes 3 1/2" (8.9 x 8.9 cm) Square Plate	250 lbs (113 kg)	4

3" or 5" Square Plate Casters w/Brakes

- Grease-resistant, non-marking, polyurethane wheels with brakes
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- Temp. range: 14°F to 212°F (-10°C to 100°C)

Item #	Description	Capacity per Caster	Case
FPCST3	Set of 4 - 3" (7.6 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes	250 lbs (113 kg)	4
FPCST5	Set of 4 - 5" (12.7 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes	250 lbs (113 kg)	4

5" Universal Square Plate Casters

- Grease-resistant, non-marking, polyurethane wheels with brakes
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- Temp. range: 14°F to 212°F (-10°C to 100°C)

Item #	Description	Capacity per Caster	Case
FPCST355	Set of 4 - 5" (12.7 cm) Universal Casters w/Brakes 3 1/2" (8.9 cm) Square Plate	250 lbs (113 kg)	4

5" Universal Rectangular Plate Casters w/Brakes

- Grease-resistant, non-marking, polyurethane wheels with brakes
- 250 lb. (113 kg) capacity per wheel
- Temp. range: 14°F to 212°F (-10°C to 100°C)

Item#	Description	Capacity per Caster	Case
FPCST2X35	Set of 4 - 5" (12.7 cm) Universal Casters w/Brakes 2 ³ /8" x 3 ⁵ /8" (6.0 x 9.2 cm) Rectangle Plate	50 lbs (113 kg)	4

3" Universal Rectangular Plate Casters*

- Polyolefin wheel casters, 2 each swivel and 2 each swivel with brakes
- 250 lb. (113 kg) capacity per wheel
- Temp. range: -20°F to +180°F (-28.9°C to +82.2°C)

Item #	Description	Capacity per Caster	Case
FPCST2X33	Set of 4 - 3" (7.6 cm) Universal Casters w/Brakes 2 ³ /8" x 3 ⁵ /8" (6.0 x 9.2 cm) Rectangle Plate	250 lbs (113 kg)	4



These casters' stainless steel mounting plates feature multiple bolt holes to fit an assortment of equipment.















*Fits Entree®

Economy Fryers