

Frymaster®

1814E

HIGH PRODUCTION, OIL CONSERVING ELECTRIC FRYERS



The Frymaster 1814E is engineered for high-volume kitchens that demand efficiency, consistency, and space optimization. With a 60-lbs. frypot and an expansive 18" x 14" cooking area, it delivers the output of larger fryers while conserving oil, energy, and floor space. Its advanced heating system and precise temperature controls ensure superior food quality and extended oil life, making it a smart choice for operators focused on performance and sustainability.

Powerful Performance, Lower Cost: 1814 electric fryers have proprietary long-life, self-standing elements that transfer 89% of the heat into the oil. Compared to conventional high-production electric fryers, this design delivers up to 30% energy savings, significantly reducing operating costs while maintaining high throughput.

More Frying Power, Less Oil Waste: The 63-lbs. frypot is optimized to create an 18" x 14" frying area that accommodates 3 baskets of product. Compared to a standard 50-lbs. fryer configuration, achieving the same output would require an additional 75 lbs. of oil—highlighting the 1814's superior oil utilization and throughput efficiency.

Maximize Output, Minimize Space: Two 1814 frypots deliver the same output as three standard 50-lbs. frypots, while using 10–15% less hood space—boosting productivity without increasing footprint.

Project _____	
Item _____	
Quantity _____	CSI Section 11400 _____
Approval _____	Date _____
MODELS	
<input type="checkbox"/> 11814E (no built-in filtration)	<input type="checkbox"/> Plug
<input type="checkbox"/> 11814EF	<input type="checkbox"/> 480V
<input type="checkbox"/> 21814EF	<input type="checkbox"/> Basket lifts
<input type="checkbox"/> 31814EF	<input type="checkbox"/> Spreader cabinet
CONTROLLERS	
<input type="checkbox"/> Lane (standard)	
<input type="checkbox"/> Digital Timer	
<input type="checkbox"/> CM3.5	
<input type="checkbox"/> 3000	

SPECIFICATIONS	
OIL CAPACITY	63-lbs. (31 liters) PER FRYPOT
FRYING AREA	18" x 14" x 4.75" (45.7 x 35.6 x 12.1 CM) PER FRYPOT
POT TYPE	Open Pot
PLUG	DOMESTIC NEMA 15-60P OPTIONAL
POWER	17 KW PER FRYPOT
STANDARD FEATURES	<ul style="list-style-type: none"> ▪ Proprietary, self-standing heating elements ▪ Deep cold zone ▪ RTD 1° compensating temperature probe ▪ Built-in, manual filtration ▪ 8 GPM pump (for all filter models) ▪ Drain safety switch (for all filter models) ▪ Stainless steel frypot, door, and sides
STANDARD ACCESSORIES	<ul style="list-style-type: none"> ▪ (3) Twin baskets PER FRYPOT ▪ Basket hanger(s) ▪ Basket support rack(s) ▪ Filter starter kit (for all filter models) ▪ 6"-7" (15-17 cm) adjustable steel legs (11814E model) ▪ Casters (all filter models)

Liter conversions are for liquid shortening @ 70° F



REVISED SPRING 2026

Frymaster®

318-865-1711
1-800-221-4583
info@frymaster.com

8700 Line Avenue
Shreveport, LA 71106-6800, USA
FRYMASTER.COM



DIMENSIONS	MODEL	OIL CAPACITY PER FRYPOT	OVERALL SIZE			DRAIN HEIGHT
			WIDTH	DEPTH	HEIGHT	
	11814E	63-lbs. (31 liters)	20.1" (51.1 cm)	30.9" (78.5 cm)	45.4" (115.2 cm)	14.63" (37.1 cm)
11814EF	20.2" (51.3 cm)		31.1" (78.9 cm)			
21814EF	40" (101.6 cm)					
31814EF	60" (152.4 cm)					

CRATED	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT	CU. FT.	CLASS
	11814E	255-lbs. (116 kg)	28" (71.1 cm)	42" (106.7 cm)	50" (127 cm)	34	85
	11814EF	390-lbs. (177 kg)					
	21814EF	585-lbs. (265 kg)	53" (134.6 cm)	44" (117.8 cm)	53" (134.6 cm)	72	77.5
31814EF	815-lbs. (370 kg)	70" (177.8 cm)	55" (139.7 cm)		98		

Information is APPROXIMATE and may vary at time of shipment due to options/add-ons

POWER	REGION	kW	ELEMENTS PER FRYPOT		CONTROLS PER FRYPOT	FILTER PER FRYPOT	BASKET LIFTS PER FRYPOT
			VOLTAGE	***3 PHASE			
	DOMESTIC	17	208V 240V 480V	48 A 41 A 21 A	1 A 1 A 120V 1 A	5 A 4 A 120V 8 A	2 A 2 A 120V/3 A
EXPORT	17	220/380V 230/400V 240/415V	26 A 25 A 24 A	1 A	4 A	2 A	

*1 PH/2 Wire/Plus Ground Wire; ***3 PH/3 Wire/Plus Ground Wire

Plug is optional on all units shipped with a cord. Canada is an exception; and cord, where available, must have a plug attached.

Cord length and gauge as well as plug type and style available vary depending upon fryer model, voltage, kW, destination, and customer specifications. Consult local codes or contact factory.

CLEARANCE INFORMATION

Front: 36" (91.4 cm) for servicing and proper operation.

Sides & Rear: 6" (15.2 cm) from any combustible material.

VENTILATION REQUIREMENTS

When installing any fryer, NFPA Standard No. 96 must be strictly followed.

NOTES

- **DO NOT CURB MOUNT**
- One cord is provided per full frypot on 3 phase units.
- Controller, filter pump and basket lifts are powered by element voltages except for 480V fryers.
- All 480 volt models are provided with separate 120V cord and plug for filter pump, controller, and/or basket lifts.

HOW TO SPECIFY

Electric or gas, gas type (if applicable), pot type, energy output, oil capacity, number of frypots, controller, filtration type, and optional feature(s).

WARRANTY

Frypot


1st year: Parts + Labor
2nd - 10th year: Parts Only

Controller

2 years: Parts + Labor

All Other Parts

1 year: Parts + Labor



Frymaster reserves the right to make changes to the design or specifications without prior notice.

REVISED SPRING 2026