

SECURITY UNITS

- **Safe Storage:** Protects valuable materials and sensitive items from loss or pilferage.
- Ready View of Contents: Heavy-gauge open wire construction keeps the entire contents of the truck visible at all times, making it easy to check inventory.
- **Durable plated finish** will not chip or flake.
- Modular offering: Build stationary or mobile security units with existing shelf, post, and caster options.
- Ergonomic, ¹/₄-Turn Door Handle: Makes opening and closing the unit easier than conventional security unit designs.
- **Double Door:** Each door opens 270 degrees and can be secured along the sides of the unit.
- Time Saving Assembly: Security units assemble quickly right out of the box.
- **Shipped Knocked-Down:** Saves on freight costs. Easily assembled.







Centaur®



Specifications

Please note: All component parts below must be purchased separately. Security Cart component parts will change based on size and choice of security unit.

Mobile:

Stationary:

Security Cage Shelves Quantity: 1
Shelves Quantity: 3-4
Mobile Posts Quantity: 4
Stem Casters Quantity: 4

Security Cart Cage Quantity: 1 Shelves Quantity: 3-4 Stationary Posts Quantity: 4

Olympic Security Enclosure Kit

Model No.		with Shelves h x Length)		Approx. Pkd. Wt.		
Chrome	(in.)	(mm)	(lbs.)	(kg)		
CSEC53-CTN	24x36	610x914	110	50		
CSEC55-CTN	24x48	610x1219	125	57		
CSEC56-CTN	24x60	610x1524	135	59		

Shelves

Model No.	•••	Nominal Size (Width x Length)			
Chrome	(in.)	(mm)	(lbs.)	(kg)	
C2436C	24x36	610x914	13	5.9	
C2448C	24x48	610x1219	16	7.3	
C2460C	24x60	610x1524	21	9.5	

Posts (Mobile and Stationary)

Stationary posts are equipped with a leveling bolt to account for uneven floors. Mobile Post are for use with Stem Casters on Mobile Security Units. Security cages are sized to work specifically with these posts.

Model No.		Height	App Pkd	rox. . Wt.
Chrome	Post Type	(in.) (m	m) (lbs.)	(kg)
C65C	Stationary	653/4 16	70 41/4	2
C63UC	Mobile	61 ¹³ / ₁₆ 15	70 31/2	1.6

Stem Casters

Model No. Chrome	Caster Type	Wheel Diameter (in.) (mm)	Face (in.) (mm)	Wheel Tread	Load Rating (lbs.) (kg)	Approx. Pkd. Wt. (lbs.) (kg)
C5	Stem/Swivel	5 127	11/4 32	Resilient	200 90	21/2 1.1
C5B	Stem/Brake	5 127	11/4 32	Resilient	200 90	2 ⁵ / ₈ 1.2

Actual Dimensions — Mobile Unit

The dimensions below assume the unit is fully assembled with top/bottom shelves, four posts, 5" (127mm) diameter casters, and Security Enclosures.

Nominal Width x Length		Actual Width		Actual	Actual Length		Actual Height	
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	
24x36	610x914	2911/16	754	403/4	1035	68 ¹ / ₂	1740	
24x48	610x1219	2911/16	754	523/4	1340	681/2	1740	
24x60	610x1524	2911/16	754	643/4	1645	681/2	1740	

Actual Dimensions — Stationary Unit

The dimensions below assume the unit is fully assembled with top/bottom shelves, four posts, and Security Enclosures.

		lominal		MC -101-				
Width x Length		Actual	(mm)		Length	Actual	Heignt (mm)	
_	(in.)	(mm)	(in.)	(111111)	(in.)	(mm)	(in.)	(111111)
	24x36	610x914	271/4	692	381/2	980	66 ¹³ / ₁₆	1695
	24x48	610x1219	271/4	692	$50^{1/2}$	1295	6613/16	1695
	24x60	610x1524	271/4	692	$62^{1}/_{2}$	1587	66 ¹³ / ₁₆	1695

