KoldFront Walk-Ins





Walk-In to Convenience!

Standard Features

- 100% foamed-in-place polyurethane panels (CFC and HCFC Free)
- Tongue and groove construction
- Cam locks create a rigid air-tight seal
- Era bracket floor
- Easier cleaning coved corners
- Energy-saving LED lighting
- Adjustable/spring-loaded hinges
- Heated air-vents on freezers
- Scroll Series (R448A) Refrigeration with scroll compressors

Specifications

Panel sizes and configurations

4" thick nominal panels that are flexible enough to be used in virtually any configuration.

Metal Finish

Interior and exterior 26 Ga Embossed Galvalume

Cooler Floor Application

Floorless: 4" vinyl screeds
***4" metal screeds required for seismic locations

Freezer Floor Application

.100 smooth aluminum Era floor

Doors

Durable FRP door perimeter and jamb. Spring loaded closer, deadbolt locking handle, adjustable hinges, interior safety release. LED door section with constant burn, low wattage nightlight

Refrigeration Systems

Pre-Charged Scroll Series (R448A) Refrigeration, medium and low temperature application packages

Popular Options to enhance the usage and performance of your walk-in.

- Air Shield
- Angle Trim
- Exterior Ramp

- Strip Door
- 1809 Compact LED light (18")

