

DIGITAL PANEL METERS

Easily monitor the internal temperature of your coolers and freezers without use in walk-in refrigerators, display cases, holding and specialty cabinets, dairy

▶ RETRO-FIT APPLICATIONS ▶ REMOTE INTERIOR TEMPERATURE READINGS



	DM450	PM120-08	PMRH120	SP120	
	Front Flange, Back Connect	Mini Rectangular, White	Mini Rectangular, Temp & Humidity	Square Solar Panel	
Temperature Range:	-40° to 450°F (-40° to 230°C)	-40° to 122°F (-40° to 50°C)	-12° to 140°F (-24° to 60°C)	-58° to 158°F (-50° to 70°C)	
Accuracy:	±2°F (±1°C) from -40° to 300°F ±2% of reading from 301° to 450°F	±1.8°F (±1°C) from -4° to 122°F (-20° to 50°C) ±3.6°F (±2°C) below -4°F (20°C)	±2°F (±1°C) ±5% RH from 30° to 75%RH/ at 32° to 122°F (0° to 50°C)	±2°F (±1°C)	
Resolution:	0.1°	0.1°	0.1°/1% RH	0.1°	
Ambient Operating Range:	0° to 150°F up to 90% non-con- densing	0° to 120°F up to 90% non-condensing	0° to 120°F up to 90% non-condensing	0° to 120°F up to 90% non-condensing	
Response Time:	30 seconds 10 second updates	30 seconds	5 seconds	30 seconds 10 second updates	
LCD:	1.3" x 0.5" (33 mm x 13 mm)	1.875" x 0.625" (48 mm x 16 mm)	1.875" x 0.625" (48 mm x 16 mm)	1.875" x 0.625" (48 mm x 16 mm)	
Lead Length:	39" (1 m)	39" (1 m)	39" (1 m)	10' (3 m)	
Case Material:	Stainless Steel	Polycarbonate	Polycarbonate	ABS	
Case Dimensions:	3.0" x 1.375" (76 mm x 27 mm)	2.7" x 1.4" x 1.1" (69 mm x 36 mm x 28 mm)	2.75" x 1.5" x 1" (70 mm x 38 mm x 25 mm)	2.75" x 2.75" x .75" (70 mm x 70 mm x 19 mm)	
Power:	(1) 1.5V #LR754	(1) 1.5V AA	(1) 1.5V AA	Solar w/ battery back-up (1) 1.5V A76	
Mounting:	Front Flange	Optional Mounting Flange (Model 9302)	Optional Mounting Flange (Model 9302)	Hangs	
Weight:	3 oz (85 g)	2 oz (57 g)	2.5 oz (71 g)	2.5 oz (71 g)	
Regulatory Listings:	CE  RoHS	CE  RoHS	CE  RoHS	CE  RoHS	
Warranty:	1 year	1 year	1 year	1 year	