





		Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
RFF1300		RFF1300A-261	Flake	Air	208-230v/60hz/1	263 lbs / 119 kg	RFS1200A-261
		RFF1300W-261	Flake	Water	208-230v/60hz/1	263 lbs / 119 kg	RFS1200W-261
		RFK01300AZ-251	Flake	Air	230v/50hz/1	263 lbs / 119 kg	RFS1200AZ-251
		RFK01300WZ-251	Flake	Water	230v/50hz/1	263 lbs / 119 kg	RFS1200WZ-251
		 Recommended Bins: D570, D970 See pages 22-23 for required adapters. Use cleaner (000000084) only with this model. Price list performance rating is 60hz data. Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce® II Not Stackable 50 Hz Electric Connection: Add Z for Bare Lead cord.					
RFF1220 / RFS1278		RFF1220C-261	Flake	Remote	208-230v/60hz/1	186 lbs / 84 kg	RFS1278C-261
		RFS1278C-251	Flake	Remote	230v/50hz/1	186 lbs / 84 kg	n/a
		**Requires RCUF1200 (60hz) or RJC 1275 (50hz) remote condensing unit and RC51 tubing kit. (see page 12)  Recommended Bins: D420, D970. See pages 22-23 for required adapters. Use cleaner (000000084) only with this model. Price list performance rating is 60hz data. Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce II. Not Stackable					
RFF2200C / RF2378C		RFF2200C-261	Flake	Remote	208-230v/60hz/1	279 lbs / 127 kg	RFS2378C-261
		RFS2378C-251	Flake	Remote	230v/50hz/1	279 lbs / 127 kg	n/a
		**Requires RCUF2200 (60hz) or RJC2375 (50hz) remote condensing unit and RC51 tubing kit. (see page 12)  Recommended Bins: D970, F1300, F1325, F1650, FC1350 See pages 22-23 for required adapters. Use cleaner (000000084) only with this model. Price list performance rating is 60hz data. Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce II. Not Stackable					

★ ENERGY STAR® Qualified Model

*Daily ice production based on air-cooled condenser model at air temperature/water temperature.