

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:			
Model #:			
Item #:			
Available W/H:		Qty:	
Approval:			
AIA#:	SIS#:		
CSI Section 11400			

Pass Thru Solid Door Heated Cabinet

Reach-In M3 Series

Model: M3H24-1-PT

___ FEATURES & BENEFITS =__

■ Digital temperature control & monitor system

- Keeps food products safe by maintaining constant temperatures
- · Alarm beeps when doors are not sealed
- · Digital display allows for easy monitoring

■ Ducted fan air distribution system

Maintains temperature within the food zone

On/Off switch

ON/OFF switch is located on control panel

Stainless steel cabinet construction

The Turbo Air M3 heated cabinet model boasts a stainless steel exterior (galvanized steel top, bottom and back) and interior. It guarantees the utmost in cleanliness and long product life. Sharp corners and edges have been rounded to reduce the risk of injury. The M3 adds a touch of style to the most refined

■ LED interior lighting

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Field reversible door hinge
- Adjustable, stainless steel wire shelves
- Heated cabinet holds 140°F ~ 180°F for the best in food preservation














Pass Thru Solid Door Heated Cabinet

Model: M3H24-1-PT

ELECTRICAL DATA		
Voltage	115/60/1	
Plug Type	NEMA 5-15P	
Full Load Amperes	8.5	
Wattage (W)	950	
Cord Length (ft.)	8	
DIMENSIONAL DATA		
# of Doors	2	
# of Racks Accepted	1	
Net Capacity (cu. ft.)	22.7	
Ext. Length Overall (in.)	283/4 (730mm)	
Ext. Depth Overall (in.)	331/8 (840mm)	
Ext. Height Overall (in.)†	78 (1981mm)	
Int. Length Overall (in.)	223/8 (568mm)	
Int. Depth Overall (in.)	245/8 (625mm)	
Int. Height Overall (in.)	583/4 (1493mm)	
# of Shelves	3	
Shelf Size (L x D) (in.)	231/2 x 215/8	
Net Weight (lbs.)	188	
Gross Weight (lbs.)	231	

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection. † Height does not include 5" for caster height.

WARRANTY: 3 Year Parts and Labor Warranty

STANDARD FEATURES

- Door locks
- 4" dia. swivel casters with locks on the front set
- · Easy replaceable one piece magnetic door gaskets
- · Solid and sturdy grille design


OPTIONAL ACCESSORIES

- 5" caster, 1/2" diameter & 13 TPI:
- M726500100 (non-brake), M726500200 (w/ brake)
- 6" stainless steel leg: 30221M0600
- · Half door bun tray rack: TSP-2224


(each holds up to six 18"L x 26"D sheet pans)


- Full door bun tray rack: TSP-2250-T
- (each holds up to fifteen 18"L x 26"D sheet pans)
- 5 pairs of universal tray slides and pilasters for M3H24-1: TS1-UNM
- · Additional stainless steel wire shelf: T24H938760

PLAN VIEW



TOP VIEW





Ver.20251031









ENERGY STAR® Qualified

■ Turbo Air: 800-627-0032 ■ Bake Tech Innovation: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002



