

|                   |        |
|-------------------|--------|
| Project:          |        |
| Model #:          |        |
| Item #:           |        |
| Available W/H:    | Qty:   |
| Approval:         |        |
| AIA #:            | SIS #: |
| CSI Section 11400 |        |

## Glass Door Worktop Refrigerator

Worktops  
**PRO Series**

**Model : PWR-48-G-N**

### Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



### FEATURES & BENEFITS

#### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Digital temperature control & monitor system

Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

#### Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a **22 gauge** stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

#### Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. Only the PRO series uniquely provides stainless steel shelving.

#### LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

#### Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

#### Spring assisted heavy duty gravity hinge

#### Refrigerator holds 33°F ~ 38°F for the best in food preservation

#### Built to maintain NSF standard temperatures in 100°F ambient



| Model             | Swing Doors | CU./FT.     | #of Shelves | HP         | AMPS       | Crated Weight (lbs.) | L x D* x H† (inches)        |
|-------------------|-------------|-------------|-------------|------------|------------|----------------------|-----------------------------|
| <b>PWR-48-G-N</b> | <b>2</b>    | <b>12.2</b> | <b>2</b>    | <b>1/6</b> | <b>6.5</b> | <b>295</b>           | <b>48 1/4 x 30 x 34 1/8</b> |

# Glass Door Worktop Refrigerator

Worktops  
PRO Series

## Model : PWR-48-G-N

| ELECTRICAL DATA            |                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------|
| Voltage                    | 115/60/1                                                                                     |
| Plug Type                  |  NEMA 5-15P |
| Full Load Amperes          | 6.5                                                                                          |
| Compressor HP              | 1/6                                                                                          |
| Cord Length (ft.)          | 10                                                                                           |
| Refrigerant                | R-290                                                                                        |
| DIMENSIONAL DATA           |                                                                                              |
| Net Capacity (cu. ft.)     | 12.2                                                                                         |
| Ext. Length Overall (in.)  | 48 1/4 (1225mm)                                                                              |
| Ext. Depth Overall (in.)*  | 30 (762mm)                                                                                   |
| Ext. Height Overall (in.)† | 34 1/8 (868mm)                                                                               |
| # of Doors                 | 2                                                                                            |
| # of Shelves               | 2                                                                                            |
| Shelf Size (L x D) (in.)   | 21 x 17                                                                                      |
| Net Weight (lbs.)          | 248                                                                                          |
| Gross Weight (lbs.)        | 295                                                                                          |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 1-7/8" for door handle & rear spacers.

† Height does not include 4-1/2" for caster height.

- **WARRANTY :** 5 Year Parts and Labor Warranty  
7 Year Compressor Warranty

### STANDARD FEATURES


- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters with locks on the front set
- Door locks

### OPTIONAL ACCESSORIES


- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" - 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Single overshef, stainless steel, 48-3/8" W: TSOS-4SW

## PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

Ver.20251231

NATURAL  
Refrigerant



- Turbo Air: 800-627-0032
- Bake Tech Innovation: 800-500-3519
- Warranty: 800-381-7770
- AC: 888-900-1002

REFRIGERATOR MANUFACTURER  
**Turbo air**

**BTI** BAKE TECH  
INNOVATION

REFRIGERATION SYSTEM  
**Turbo air** **texaking**

Continued product development may necessitate specification changes without notice.