



UR60B

Undercounter 60" Refrigerator



UR60B
06/27/25
Item # 13627

W x D x H
60" x 30" x 33.75"*
*with 4" casters



Dimensions / Capacity

Interior Storage Capacity (CF) (AHAM)

Overall Width x Depth (including 1" bumper)

Height (including 4" casters)

Door Opening Width x Height

Depth with Door Open at 90° (including 1" bumper)

Adjustable Shelves

Shelf Dimensions (W x D)

Crated Weight

Crated Length x Width x Height

One-Section UR60B

15.1 ft³

60" x 31"

33.75"

25.5" x 23"

58.5"

2

27.25" x 16"

290 lbs.

62.5" x 34" x 36.5"

Electrical / Refrigeration

Voltage

HACR Breaker

Electrical Connection (NEMA)

Voltage Range

Ambient Temp. Range

Control Setpoint Range

Amperage

Energy Consumption (kWh/day) @ASHRAE

Heat Rejection (BTU/Hr.) @NSF

Approx. Nominal Compress. BTU/HR (HP)

Refrigerant / Charge Amount (oz)

One-Section UR60B

115/60/1

15.0 Amps

5-15P Ⓢ

104-126

45° to 100°F

32° to 52°F

3

0.927

249

798 (1/5HP)

R290 (2.3 oz)

Options

☐ 2.25" Casters

☐ 6" Casters

☐ Stacking kit (HS-5112)

☐ Cylinder locks (-01 factory installed)*

* SPECIAL ORDER- Allow 4-6 weeks lead time.

☐ Additional epoxy shelves

☐ Stainless steel shelves

☐ Overshelves

☐ Foot pedal (right mount)

☐ Foot pedal (left mount)



Seven year warranty on labor, parts, and compressor. Valid in United States, Canada, Puerto Rico and U.S. Territories.

For more information, please visit hoshizakiamerica.com/support/warranty/

Item #: _____

Project: _____

Qty: _____

AIA#: _____

Features

► Engineered to maintain NSF-7 temperatures in 100°F ambient.

► Stainless steel exterior front, sides, and top with stainless steel interior sides, back, and floor

► Front breathing air flow design

• Environmentally friendly R290 hydrocarbon refrigerant

• Cabinet and doors are insulated with 2" CFC free, foamed in place polyurethane

• Exclusive "stepped" door design to protect door gasket

• Spring assisted self-closing doors with stay open feature

• Extruded aluminum flush mount door handle

• Field reversible doors

• Magnetic door gasket is easily removable for cleaning

• Hot gas condensate removal

• E-coated evaporator coil

• One epoxy coated shelf per section is standard

• Anodized aluminum shelf supports adjustable in 1/2" increments

• Standard with 4" casters (two with brakes)

• 10 ft. cord and plug



UR60B



Undercounter 60" Refrigerator




UR60B
06/27/25
Item # 13627

FRONT VIEW

SIDE VIEW



PLAN VIEW



Cabinet Construction

The exterior cabinet top, front, and sides, are constructed of high quality stainless steel. The exterior back and bottom are constructed of coated steel. The cabinet interior features stainless steel back, sides, and floor with an ABS top. One heavy duty epoxy coated shelf per section is standard. Mounted on anodized aluminum pilasters the shelves are adjustable in $\frac{1}{2}$ " increments. Cabinet walls are insulated with 2" CFC free, foamed in place polyurethane. 4" polyolefin, stem casters (two with brakes) are standard.

Door Construction

Doors are constructed of high grade stainless steel exterior with an ABS interior liner and are insulated with 2" CFC free, foamed in place polyurethane. Hoshizaki's exclusive "stepped" design protects the gasket while product is removed from the cabinet. Doors are provided with a one piece, extruded aluminum, flush mount handle. Spring assisted self-closing doors are equipped with a stay open feature past 90 degrees. Snap-in magnetic door gaskets are durable and easily removed for cleaning. Field reversible door hinging is standard.

Refrigeration System

The high efficiency refrigeration system is self-contained with an E-coated evaporator for extended life. Condensate removal is accomplished with an energy efficient non-electric evaporation system. A capillary tube controls the flow of environmentally friendly R290 refrigerant through the evaporator. Refrigeration system utilizes an "off cycle" defrost to eliminate any ice on the evaporator coil. 115 volt units are equipped with a ten foot cord and plug (20.0 amps or less).