


iT0420 Series



W 22" D 24.5" H 21.5"
W 55.9 D 62.2 H 54.6 cm

*460 lbs/209 kg daily at 70/50°F
*375 lbs/170 kg daily at 90/70°F



Not Stackable

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
IDT0420A-161	Dice	Air	115v/60Hz/1	137 lbs / 62 kg	ID0322A-161
IDT0420A-161X	Dice	Air	115v/60Hz/1	142 lbs / 64 kg	ID0322A-161X
IDT0420A-261	Dice	Air	208-230v/60hz/1	137 lbs / 62 kg	ID0322A-261
IDT0420W-161	Dice	Water	115v/60Hz/1	131 lbs / 59 kg	ID0323W-161
IYT0420A-161	1/2 Dice	Air	115v/60Hz/1	136 lbs / 62 kg	IY0324A-161
IYT0420A-161X	1/2 Dice	Air	115v/60Hz/1	141 lbs / 64 kg	IY0324A-161X
IYT0420W-161	1/2 Dice	Water	115v/60Hz/1	135 lbs / 61 kg	IY0325W-161
IYT0420W-261	1/2 Dice	Water	208-230v/60hz/1	135 lbs / 61 kg	IY0325W-261
IDT0420A-251	Dice	Air	230v/50hz/1	137 lbs / 62 kg	ID0322A-251
IYT0420A-251	1/2 Dice	Air	230v/50hz/1	136 lbs / 62 kg	IY0324A-251


If factory installed LuminIce II not offered, use aftermarket kit found on page 24.

Recommended Bins: D320 or D420 (see page 19).

See pages 22-23 for required adapters, deflectors, and dispenser baffles.

Price list performance rating is 60hz data. Refer to individual 50hz spec sheets for 50hz performance rating.

iT0450 Series



W 30" D 24.5" H 21.5"
W 76.2 D 62.2 H 54.6 cm

*490 lbs/222 kgs daily at 70/50° F
*378lbs/171 kg daily at 90/70° F



Not Stackable

IDT0450A-161	Dice	Air	115v/60Hz/1	160 lbs / 73 kg	ID0452A-161
IDT0450A-161X	Dice	Air	115v/60Hz/1	165 lbs / 75 kg	ID0452A-161X
IDT0450A-261	Dice	Air	208-230v/60hz/1	160 lbs / 73 kg	ID0452A-261
IDT0450W-161	Dice	Water	115v/60Hz/1	141 lbs / 64 kg	ID0453W-161
IDT0450W-161X	Dice	Water	115v/60Hz/1	146 lbs / 66 kg	ID0453W-161X
IDT0450W-261	Dice	Water	208-230v/60hz/1	141 lbs / 64 kg	ID0453W-261
IYT0450A-161	1/2 Dice	Air	115v/60Hz/1	170 lbs / 77 kg	IY0454A-161
IYT0450A-161X	1/2 Dice	Air	115v/60Hz/1	175 lbs / 79 kg	IY0454A-161X
IYT0450A-261	1/2 Dice	Air	208-230v/60hz/1	170 lbs / 77 kg	IY0454A-261
IYT0450W-161	1/2 Dice	Water	115v/60Hz/1	155 lbs / 70 kg	IY0455W-161
IYT0450W-161X	1/2 Dice	Water	115v/60Hz/1	160 lbs / 73 kg	IY0455W-161X
IDT0450A-251	Dice	Air	230v/50hz/1	160 lbs / 73 kg	ID0452A-251
IDT0450W-251	Dice	Water	230v/50hz/1	141 lbs / 64 kg	ID0453W-251
IYT0450A-251	1/2 Dice	Air	230v/50hz/1	170 lbs / 77 kg	IY0454A-251


If factory installed LuminIce II not offered, use aftermarket kit found on page 24.

Recommended Bins: D400 or D570 (see page 19).

See pages 22-23 for required adapters, deflectors, and dispenser baffles.

Price list performance rating is 60hz data. Refer to individual 50hz spec sheets for 50hz performance rating.

iT0500 Series



W 30" D 24.5" H 21.5"
W 76.2 D 62.2 H 54.6 cm

*550 lbs/249 kg daily at 70/50°F
*440 lbs/200 kg daily at 90/70°F



Not Stackable

IRT0500A-161	Regular	Air	115v/60Hz/1	162 lbs / 73 kg	IR0500A-161
IRT0500A-261	Regular	Air	208-230v/60hz/1	162 lbs / 73 kg	IR0500A-261
IRT0500W-161	Regular	Water	115v/60Hz/1	158 lbs / 72 kg	IR0501W-161
IDT0500A-161	Dice	Air	115v/60Hz/1	157 lbs / 72kg	ID0502A-161
IDT0500A-161X	Dice	Air	115v/60Hz/1	162 lbs / 73 kg	ID0502A-161X
IDT0500A-261	Dice	Air	208-230v/60hz/1	157 lbs / 72kg	ID0502A-261
IDT0500W-161	Dice	Water	115v/60Hz/1	163 lbs / 74 kg	ID0503W-161
IDF0500N-161A	Dice	Remote	115v/60Hz/1	164 lbs / 74 kg	IDT0500N-161
IDF0500N-161AX	Dice	Remote	115v/60Hz/1	169 lbs / 77 kg	IDT0500N-161X
IYT0500A-161	1/2 Dice	Air	115v/60Hz/1	159 lbs / 72 kg	IY0504A-161
IYT0500A-161X	1/2 Dice	Air	115v/60Hz/1	164 lbs / 74 kg	IY0504A-161X
IYT0500A-261	1/2 Dice	Air	208-230v/60hz/1	159 lbs / 72 kg	IY0504A-261
IYT0500W-161	1/2 Dice	Water	115v/60Hz/1	161 lbs / 73 kg	IY0505W-161
IYF0500N-161A	1/2 Dice	Remote	115v/60Hz/1	161 lbs / 73 kg	IYT0500N-161
IYF0500N-161AX	1/2 Dice	Remote	115v/60Hz/1	166 lbs / 75 kg	IYT0500N-161X
IRT0500A-251	Regular	Air	230v/50hz/1	162 lbs / 73 kg	IR0500A-251
IDT0500A-251	Dice	Air	230v/50hz/1	157 lbs / 72kg	ID0502A-251
IYT0500A-251	1/2 Dice	Air	230v/50hz/1	159 lbs / 72 kg	IY0504A-251

If factory installed LuminIce II not offered, use aftermarket kit found on page 24.

Recommended Bins: D400, D570 or F700 (see page 19).

See pages 22-23 for required adapters, deflectors, and dispenser baffles.

¹Use JCF0500 remote condenser and RT() R404A tubing kit (see page 10).

Price list performance rating is 60hz data. Refer to individual 50hz spec sheets for 50hz performance rating.