

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

## MARKETMAX DUAL-TEMP REFRIGERATOR/REFRIGERATOR

MMRR49HC Black Hinged Double Glass Door Hydrocarbon Series

MODEL: MMRR49HC-1-A-BW



7 Year Parts/Labor Warranty7 Year Compressor Warranty

#### **CABINET CONSTRUCTION**

- Exterior features durable black painted steel
- Heavy-duty interior construction includes white coated steel walls
- Brightly lit sign panel
- LED lighting
- Modern one-piece grille
- · Full electronic control with digital display
- Dual-temp refrigerator/refrigerator units provide two different operating temperature zones for different types of products
- · Self-contained bottom mount refrigeration system
- · Refrigerators have double pane lowE argon filled glass doors
- Self-closing doors with 120° stay-open feature
- Snap-in gaskets, easy to remove for cleaning or replacement
- Ten (10) heavy-duty epoxy coated wire shelves
- Four (4) shelf clips included per shelf
- Leveling feet standard

#### **OPTIONS & ACCESSORIES**

- Stainless steel or white exterior
- · Stainless steel or black interior
- Shelves black or white
- Shelf clips
- Flow track
- Gravity-Flo track
- Price tag molding
- 3" or 6" Casters
- 6" Legs or seismic/flanged legs
- Door locks (swing doors only)
- Custom signage & decals
- Remote option\* (see note on back on page)

#### **REFRIGERATION SYSTEM**

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Non-electric defrost with hot gas condensate evaporation
- Epoxy coated evaporator coil
- Maintains product temperatures between 36°F to 38°F








MODEL	MMRR49HC-1-A-BW	
EXTERNAL DIMENSIONAL DATA		
Width Overall	52"	
Depth Overall (with handle)	33 ½"	
Height Overall	78 ½"	
Number of Doors	2	
Depth with Door Open 90°	56 ½"	
Door Openings (in)	22 ¾" x 52 ¾"	
INTERNAL DIMENSIONAL DATA		
NET Capacity Refrigerator (cubic ft.)	21.01	
NET Capacity Refrigerator (cubic ft.)	21.01	
Internal Width Overall (in)	(2) 23"	
Internal Depth Overall (in)	27"	
Internal Height Usable (in)	55"	
Number of Shelves	10	
ELECTRICAL DATA		
Full Load Amperes	R 3.18 - R 3.18	
Voltage	115/60/1	
Nema Plug (8' cord)	(2) 5-15P	
REFRIGERATION DATA		
Horsepower	(R) 1/4 (R) 1/4	
Capacity (BTU/Hr)	(R) 1702 (R) 1702	
Heat Rejection (BTU/Hr)	4848	
Charge (lbs/grams/ounces)	(R) 0.1984 / 90 / 3.17 (R) 0.1984 / 90 / 3.17	
SHIPPING DATA		
Gross Weight (crated lbs)	708 lbs	
Height - Crated	85"	
Width - Crated	56"	
Depth - Crated	36"	

\*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4°. Metric dimensions (MM).

# Dual-Temp Glass Door Merchandisers Model: MMRR49HC-1-A-BW





### **ELECTRICAL CONNECTION**



115/60/1 (2) NEMA 5-15P Unit pre-wired at factory and include 8' long cord and plug set.



