## PIZZA PREPARATION TABLE

## **Model: PA43N**

Natural Refrigerant R-290 Model

## 43" Pizza Preparation Refrigerator with Solid Doors

Heavy gauge #300 series stainless steel top, stainless steel front and end panels, aluminum interior.



## **Options and Accessories**

(upcharge and lead times may apply)

Stainless steel interior	Pan slides
Stainless steel back	Wire rod garnish rack
Overshelves (single or double)	Vision panel lid
Additional epoxy coated steel shelves	Door locks
Stainless steel shelves	Adjustable legs
Condensing unit on left (standard on right)	Front breathing
Drawer in lieu of half door above the condensing unit*	Special electrical requirements (consult factory)

<sup>\*</sup>Drawer section above condensing unit holds (1) 12 x 20 x 6 pan

Drawers in lieu of doors\*\*

<sup>\*\*</sup>Two tier (larger section) holds (2) 12x20x6 pans per drawer
Consult factory for other model configurations, options and accessories





Project Name:	
Model Specified:	
Location:	
Location.	
Item No:	Quantity:
AIA #:	SIS #:

## **Standard Model Features**

#### REFRIGERATION SYSTEM

Performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Unique forced air design utilizes fans (approx. every 12") across the entire back of unit for even distribution of cold

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide out condensing unit

Expansion valve system

#### **CABINET ARCHITECTURE**

2" non-CFC polyurethane foam insulation

Smooth, polished chrome door handles

Spring loaded, self closing doors

Magnetic snap in Santoprene™ door gaskets

Heavy duty, epoxy coated steel shelves

19" deep, full length nylon cutting board with hold down clips

Insulated lids (with heavy duty hinge pins)

(4) pan top divider bars\*

5" casters

\* Pans supplied by others

#### **MODEL FEATURES**

Reversing condenser fan<sup>2</sup>

Ergonomically-friendly raised angle rail

Electronic control, off-cycle defrost

Refrigerated section with door above the condensing unit

Field rehingeable doors

NOTE: Models come standard with a door above the condensing unit. A drawer above the condensing unit is an option.

APPROVAL:

<sup>&</sup>lt;sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

<sup>&</sup>lt;sup>2</sup> Fan runs in reverse for short period on startup to blow away any debris.

## **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	12 (340 I)
Width, Overall (inches)	43 (1092 mm)
Depth, Overall (inches) (including cutting board & bumpers)	38 ¾ (972 mm)
Height, Overall (inches) (including 5" casters)	39 (989 mm)
Depth, Cutting Board (inches)	19 (483 mm)
Shelf Area (square feet)	5.6 (0.5 sq m)
Number of Shelves	1
Number of Full Doors	1
Number of Half Doors	1
Interior Depth (inches)	27 3/8 (695 mm)
Interior Height (inches)	26 (660 mm)
Interior Height (inches)	12 ½ (318 mm)
(above condenser)	
PAN TOP	

#### **REFRIGERANT DATA**

Divider Bars (supplied with model)

Pan Capacity (pans supplied by others)

Condensing Unit Size (H.P.)	1/4+
Capacity (BTU per hour)*	1930
ELECTRICAL DATA	

#### **ELECTRICAL DATA**

Voltage (International)	115/60/1 (220/50/1)
Total Amps (International)	5.5 (4.7)
10 ft. Cord/Plug [attached] (International)	Yes (No)

#### **SHIPPING DATA**

Weight (pounds)	325 (147 kg)
Height - Crated (inches)	43 ¾ (1111 mm)
Width - Crated (inches)	45 (1143 mm)
Depth - Crated (inches)	47 (1194 mm)

<sup>\*</sup> Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)

# Continental® Refrigerator

**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

(4) CM1-0111

(4) 1/3 & (1) 1/2

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

## **Model Plan Views**





**IMPORTANT NOTE:** If the cabinet is located directly against a wall, a <u>minimum clearance of 3" is required</u> on sides, front and rear.