

## DSLHRI Roll-Ins

Heated Roll-In w/Glass Doors

#### Models

☐ DSLHRI1-G ☐ DSLHRI2-G



DSLHRI2-G

#### Standard Features

- Stainless steel exterior and interior
   Touch Control with remate
- easyTouch Control with remote monitoring capability
- Stay-open door feature for easy product loading and unloading
- · Door activated interior LED light
- Heavy-duty cylinder lock
- · Stainless steel interior door liner
- · One piece, snap-in door gaskets
- Stainless steel breaker caps3 silver freeze wire shelves
- 8' cord and plug
- Adjustable Electronic Temp Control From 80°F To 180°F
- Built-In, Adjustable Humidity Control
  Vent
- Safety Shielded Strip Type Heating Elements
- Externally Mounted Blower Maintains Even Temperatures
- Accepts Carts: 26 1/2" w x 28" D x 65" H (cart not included)
- Three year parts and labor warranty and an additional 4 year compressor parts warranty.

# Options & Accessories


- Stainless Steel Back And Shroud
- Door Swing Orientation (at time of order)
- Exterior Door Laminate
- Correctional Package

#### Specifications

**Heating system:** Cabinets are designed to maintain temperatures between 80°F - 180°F. Units are heated with two bottom-mounted heating elements per section. The externally mounted blower allows for full use of interior cabinet while maintaining even temperatures. System is controlled using an electronic temperature control.












## **Delfield**°


#### DSLHRI1-G








### DSLHRI2-G





Specifications								
Model	V/Hz/Ph	Amps	Volume Cu. Ft.	SHELF CAPACITY SQ. FT.	No. of Shelves	Heater Watts	Ship Weight	Nema Plug
DSLHRI1-G	208-240/60/1	6.8	33.6	N/A	N/A	1500	355	6-20P
DSLHRI2-G	208-240/60/1	13	67.2	N/A	N/A	3000	560	6-20P

Welbilt reserves the right to make changes to the design or specifications without prior notice.

