

## Tray Delivery Carts

### Power Tug (See page 51)

- Reduces risk of injuries due to pulling and pushing
- Increases productivity
- Tows up to 1500 lbs.
- Can tow single and multiple carts with the use of available hitches and hitch receiver tubes

*Freight Class 92.5*



MODEL	TOW CAPACITY	ELECTRICAL	LENGTH	DEPTH	HEIGHT	CASE WEIGHT
EPT	1500 lb.	2 Ea. 22 Amp Rechargeable 24 VAC Drive Batteries	18-3/4	24	42-1/2 in.	150 lbs.

### Universal Hitch System (See page 51)

The Universal Hitch System allows the Power Tug to tow virtually any piece of mobile equipment. Simply install a Receiver Tube to the bottom side of the mobile equipment, then insert a component Hitch.



#### Receiver Tubes

MODEL	DESCRIPTION	ADJUSTABLE LENGTH
RTB*	Bolt-On Receiver Tube	N/A
RT26	Adjustable Clamp-On Tube (Small)	26" to 41"
RT40	Adjustable Clamp-On Tube (Medium)	40" to 55"
RT56	Adjustable Clamp-On Tube (Large)	56" to 76"

*\*Specify tube length required for non pass thru models only.*

#### Hitches

MODEL	DESCRIPTION
MH5	Male Hitch (5" or 6" Casters) For Towing Single Pieces
MH6	Male Hitch (6" or 8" Casters) For Towing Single Pieces
FH	Female Hitch For Towing Multiple Pieces

### Tray Cart Options

MODEL	DESCRIPTION	FITS CART MODEL(S)
WB	Wrap around bumper for single compartment	RS, TDC
CB	Corner bumper	TDC, RS
TR1	Top Rail 1 sided	RS, TDC**
TR2	Top rail 2 sided	RS, TDC**
TR3	Top rail 3 sided	RSDC, RS, TDC**
TR4	Top rail 4 sided	RS, TDC**
8C	8" casters	ETC, TC, VL, TDC
TL	Transport Latch	ETC, TC, VL
MCH	Menu Card Holder	ETC, TC, VL
FD	Floor drain	TC, RS, TDC
TH	Tow hitch	ETC, TC, TDC
PH	Push Handle	RS, TDC*
CLS	Custom ledge spacing	ETC, TC, VL
STATS	Anti Static Strip	All Models

*\*Push handle for non pass thru capacities 16, 20, and 24 \*\*Top rails for up to 14 capacity carts*