

Master CG Series Gas Front Drain Production Griddle

Project _____
 Item _____
 Quantity _____
 CSI Section 11400
 Approved _____
 Date _____

Models

- CG-48F
- CG-60F
- CG-72F



Model CG-60F
Shown with 4"(102mm) legs

Standard Features

- Standard Features:
- Front, full width grease trough with integral front rail
- 1" (25mm) polished finish steel plate
- One "U" shaped 30,000 BTU (8.8kW) burner Every 12" (305mm) of Griddle width
- Flame-failure protection on all burners
- Electronic controls
- Electric main on/off power switch w/ indicator light. Requires 120V 60Hz
- Electronic thermostat 150°F (101°C) to 450°F (268°C) for each burner every 12" (305mm)
- Amber lamp for each section showing when the system is on
- Green lamp for each pilot indicating pilot is on
- Stainless steel sides
- Stainless steel side griddle splash guards, 3" (76mm) high
- Stainless steel, 6" grease drawers with integral grease baffle, capacity 1.6 gal/6 L.
- Stainless steel grease chute extensions for easy drainage into separate container
- 6" (152mm) high stainless steel adjustable legs
- Nickel-plated thermostat guards
- Combination gas regulator/solenoid valves to control gas flow to burners and pilots
- 7.6" (190.5 mm) high back splash

Options & Accessories

- 20-240 Volts, 60 Hz, no charge
- Protective shield for controls
- 10-1/2" (266mm) deep grease drawers , no charge (stand models only). 2.36 gal/8.9 L
- Stainless steel open stand, 30" (769mm) high with stainless steel bottom shelf on adjustable legs or casters (specify).
- 4" (102mm) high stainless steel adjustable legs & 3-1/4" (83mm) high grease drawer, ideal for refrigerated equipment base mounts. Grease drawer capacity 1.4 gal/5.25 L.
- Chromed griddle

Specifications

Heavy-duty gas griddles (available in three sizes, 48", 60", and 72").

High performance volume production with even, consistent, controlled temperatures.

1" (25mm) thick griddle plate.

Electronic thermostat with embedded sensor and efficient 'U' shaped burner every 12"(205mm) of griddle width.

All stainless steel exterior.


Full width front rail.

6" (152mm) legs standard.



NOTE: Griddles supplied with casters must be installed with an approved restraining device.



Master CG Series Gas Front Drain Production Griddle



This product must be installed by professional personnel as specified. Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland/U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications.



Optional 4" (102mm) high stainless steel adjustable legs & 3-1/4" (83mm) high grease drawer.

| | | | | |
|---|---------------------|---|----------------|---|
| Installation Notes | | Entry Clearance | | Electrical Characteristics |
| Combustible Wall Clearances | | Crated | UnCrated | Specifications |
| Sides 6" (152mm) | Back: 6" (152mm) | 40" (1016mm) | 38" (915mm) | 120 V, Single Phase, 60Hz, 1 amp 6' (1829mm) power supply cord provided |
| • IMPORTANT: A minimum 4" (101mm) air space must be maintained below unit for required air flow to burners. | | • See Illustration for further specifications & size statistics | | • NOTE: Optional 208-240 volt 60 Hz 0.4 amps, single. No cord & plug supplied |

| | | | |
|---|--------------------|----------------------------------|---------------------|
| Manifold Pressure Required, After Built- In Regulator | | Minimum Supply Pressure Required | |
| Natural | Propane | Natural | Propane |
| 3.5" W.C. (8.75 mbar) | 10" W.C. (25 mbar) | 7" W.C. (17.4mbar) | 11" W.C. (27.4mbar) |

| Input Chart - Natural Or Propane Gas | | | | | |
|--------------------------------------|-----------|-------|-----------|-----------------|------|
| Model Number | BTU/ Hour | Kw | Gas Inlet | Shipping Weight | |
| | | | | Lbs. | Kgs. |
| CG-48F | 120,000 | 35.00 | 3/4" | 625 | 284 |
| CG-60F | 150,000 | 44.00 | 3/4" | 765 | 348 |
| CG-72F | 180,000 | 52.70 | 1" | 905 | 411 |

• Gas Input Ratings shown are for installations up to 2,000 feet (610mm) above sea level. BTU input ratings must be derated for high altitude installations. Please specify gas type..

Garland reserves the right to make changes to the design or specifications without prior notice.