Fusion

GHPF 52"H Dry Self-Service Case



GHPF452LB
GHPF552LB
GHPF652LB
GHPF652LB
GHPF852LB
GHPF852LB
GHPF852LB
GHPF852LB
GHPF852LB

Included

- Flat swing-out front glass
- LED top & shelf lights
- · Non-refrigerated for ambient display
- One year parts & labor warranty
- Powder coated Silversan Black rear exterior




Specify	Standard Features	Additional Options
EXTERIOR COLOR	Laminate (stock colors)	Laminate (non-stock colors)
INTERIOR COLOR	Powder coated Silversan Black	
LOWER FRONT PANEL COLOR	Powder coated Silversan Black	Powder coated (stock/non-stock colors)
		Stainless steel
BASE SUPPORT	Rail system for shims	
BUMPER FRONT	1" Boston bumper (specify color)	1" Stainless steel plate rail bumper
END PANELS	Full w/stainless steel mirror interior	None (specify per line-up)
PACKAGE AREA	Tissue box and bag holder	• (2) Tissue box holders
PRICE TAG MOLDING	• None	1" Price tag molding (black or silver)
		Universal price tag molding (clear w/ open top)
REAR DOORS	None (solid back panel)	Reflective glass rear sliding doors
SHELVING	Wire rack shelves (3)	Wire rack shelves (4)
LIGHTS	LED 3500K w/ frosted lens	• LED 4000K w/ frosted lens
ELECTRICAL CONNECTION	Electrical leads	
MISCELLANEOUS		2"H Black wire baskets
		4"H Black wire baskets
		• 9"X 26" Trays
		Front glass lock
		Rear door lock


Structural Concepts

DELIVERING FRESH. ALWAYS.™


Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.					
Z	Zone	Intended Product To Be	Displayed	Warmest Avg Prod Temp ° F	
	1	Packaged / unpackaged	non-refrigerated products	Ambient	


PLAN VIEW






3 LEVELS OF SHELVING W/4"H BASKETS







NOTE: ALL DIMENSIONS APPROXIMATE

ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD). LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3/4" OR 11/2" PVC TUBE).

REFRIGERATION LINE CONNECTION.

REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

SELF-CONTAINED CASE SERVICE ACCESS AREA.

DRY CASE SERVICE ACCESS AREA.

	Model Technical Specifications															
Model	L"	L1"	L2"	System Circu	it Volts		Phs	Freq	Amps	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack RTUH	Est Wt
GHPF452LB	48.75	51.00	.00	Ambient/Lights (N/A)	Circuit #1	110-120	1	60	0.70	25	2+G	Leads Single	N/A	N/A	N/A	750
GHPF552LB	60.50	62.75	.00	Ambient/Lights (N/A)	Circuit #1	110-120	1	60	0.70	40	2+G	Leads Single	N/A	N/A	N/A	850
GHPF652LB	73.13	75.38	.00	Ambient/Lights (N/A)	Circuit #1	110-120	1	60	0.70	38	2+G	Leads Single	N/A	N/A	N/A	950
GHPF852LB	97.50	99.75	.00	Ambient/Lights (N/A)	Circuit #1	110-120	1	60	1.40	88	2+G	Leads Multiple	N/A	N/A	N/A	1,150

*** Does not include electric defrost on freezer models.

Regulatory Approvals:					
All Models	ETL Listed to UL 65				
	ETL Sanitation to NSF/ANSI 2				



DOE 2017

Important Notes:

- 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle.
- 2) 47" minimum door entry clearance required (without shipping skid).
- 3) Units must be shimmed during installation to ensure the unit is level and plumb.

▲ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.