

Project		
AIA#	SIS#	
Item #	Quantity	C.S.I. Section 114000

R Series

30" Wide Reach-In Refrigerator 26" Deep, Solid Door, Self-Contained











Models listed to the applicable UL, CSA and NSF standards by an approved NRTL. Consult the factory or unit data plate for additional information.

AVAILABLE CONFIGURATIONS

R Series Models
RHT126WUT-FHS
RHT126WUT-HHS

Door(s)Full Height Solid
Half Height Solid

*Remote application available, see form TR35837 for details.

STANDARD PRODUCT FEATURES

- Stainless Steel Exterior & Interior
- Variable Speed Compressor Adapts to the Work Environment
- Traulsen's Smart Control™ with LED Display
- Balanced, Self-Contained Refrigeration System Using R-290
- Full or Half-Height Stainless Steel Door(s) with Lock(s)
- Anti-Condensate Door Perimeter Heater
- Self-Closing Door with Stay Open Feature
- Standard Door Hinging: 126W = Right (other hingings available)
- Automatically Activated LED Lights
- Stainless Steel Breaker Caps
- Three Adjustable, Coated Wire Shelves Per Section, Supported on Shelf Pins (factory installed)
- Automatic Non-Electric Condensate Evaporator
- Magnetic Snap-In EZ-Clean™ Door Gasket
- Gasket-Protecting Raised Door Liner
- Thermostatic Expansion Valve Metering Device
- Stainless Steel One-Piece Louver Assembly
- 9' Cord & Plug Attached
- Set of (4) 6" High Adjustable Stainless Steel Legs

ACCESSORIES & OPTIONS

- SmartConnect™ Monitoring App with Wi-Fi Connectivity
- Stainless Steel Finished Back with Rear Louvers
- Option to Relocate Electrical Box
- Optional Door Hinging
- Re-Hinging Feature for Door(s)
- Additional Coated Wire or Optional Stainless Steel Shelves
- Stainless Steel Banking Strip
- EZ-Open™ Foot Pedal (full-height doors only)
- Positive Action Latch (consult factory)
- Locking Hasps (padlock supplied by others)
- Kool Klad™ Exterior Laminate Decor (consult factory)
- Set of (4) 41/8" or 6" High Casters in Lieu of Legs
- 6" Stainless Steel Flanged Legs
- Other Support Options: 4¹/₂" High Base or 6" High Kickplate (for use with standard legs)
- Prison/Correctional Facility Options
- Heat Shield



ENERGY STAR® Listed Commercial Refrigerator For full listing visit energystar.gov


- GUARANTEED FOR LIFE CAM-LIFT HINGES
- GUARANTEED FOR LIFE HORIZONTAL WORKFLOW DOOR HANDLES

Approved by	Date	Approved by	Date



MODELS:

RHT126WUT-HHS, RHT126WUT-FHS





MODELS:

RHT126WUT-HHS, RHT126WUT-FHS

MODELS	RHT126WUT	
DIMENSIONAL DATA		
Net capacity cu. ft.	18.35 (519.6 cu l)	
Length - overall in.	29 ⁷ / ₈ " (75.9 cm)	
Depth - overall in.	29" (73.6 cm)	
Depth - over body in.	26" (66 cm)	
Depth - door open 90° in.	51 ¹¹ / ₁₆ " (131.3 cm)	
Clear door width in.	21 ¹ / ₂ " (54.6 cm)	
Clear half-door height in.	27 ¹ / ₂ " (69.9 cm)	
Clear full-door height in.	57 ⁵ /8" (146.3 cm)	
Height - overall on 6" legs²	83 ¹ / ₄ " (211.5 cm)	
No. Standard Shelves	3	
Shelf area sq. ft. ³	10.46 (0.97 sq. m)	
ELECTRICAL DATA		
Voltage Plug	115/60/1 NEMA 5-15P	
Full Load Amperes kWh/24HR4	7 2.16	
REFRIGERATION DATA		
Refrigerant	R-290	
Refrigerant Charge Amount oz.	3.8 (107.7 g)	
BTU/HR H.P. ¹	1560 1/3	
SHIPPING DATA		
Length - Crated in.	48" (121.9 cm)	
Width - Crated in.	42" (106.7 cm)	
Height - Crated in.	85" (215.9 cm)	
Volume - Crated cu. ft.	99 (2803.4 cu l)	
Weight - Crated lbs.	420 (190.5 kg)	

NOTES: Figures in parentheses reflect metric equivalents.

- 1. Based on a 90°F ambient and 20°F evaporator.
- 2. 12" Top clearance preferred for optimum performance & service access.
- Area of standard shelf compliment only, does not include storage area of additional shelves or available on cabinet bottom.
- 4. kWh/24HR = Kilowatt usage per 24 hours.

EQUIPMENT SPECIFICATIONS

CONSTRUCTION, HARDWARE, INSULATION

The interior is made from stainless steel and the cabinet exterior front, one piece sides, louver assembly, door and door liner is constructed of heavy gauge stainless steel. The exterior cabinet top, back & bottom are constructed of heavy gauge galvanized steel. A set of four (4) adjustable 6" high stainless steel legs are included.

Door is equipped with a gasket-protecting metal door pan, removable plug cylinder locks & guaranteed for life gravity action, self-closing metal, camlift hinges with a stay open feature. Hinges include a concealed switch to automatically activate the interior LED lighting. Guaranteed for life, workflow door handle is mounted horizontally over recess in door which limits protrusion from door face into aisleways. Doors have seamless, polished metal corners.

Gasket profile & EZ-Clean™ material simplify cleaning & increase overall gasket life. Anti-condensate heaters are located behind the door opening. Both the cabinet & door is insulated with an average of 2" thick high density, non-CFC, foamed in place polyurethane.

SELF-CONTAINED REFRIGERATION SYSTEM

A top mounted, self-contained, balanced refrigeration system using environmentally friendly, low GWP R-290 refrigerant is conveniently located behind the one piece louver assembly. It features a thermostatic expansion valve, air-cooled hermetic variable speed compressor, large, high humidity evaporator coil located outside the food zone & top mounted non-electric condensate evaporator. A 9' cord & plug is provided. Standard operating temperature is 34-38°F.

CONTROL

Traulsen's Smart Control™ features advanced control algorithms & sophisticated diagnostic capabilities to optimize performance. Utilizing smart sensors, it adapts the operation of the refrigeration system to a variety of environments & usage patterns. The Smart Control™ also offers a complete set of visual alarms designed to alert the user to critical events such as power outages or a prolonged door opening. In the event of an alarm, a dedicated Alarm LED will illuminate, informing the user of the critical event and duration.

INTERIOR

Standard interior arrangements include three (3) coated wire shelves per section, mounted on shelf pins. Shelves are full-width & do not have any large gaps between them requiring the use of "bridge" or "junior" shelves. Recommended load limit per shelf should not exceed 225 lbs. Interior arrangements are installed at the factory.

WARRANTY

Both a six year parts and labor warranty and a seven year compressor warranty (self-contained models only) are provided standard.

When ordering please specify: Voltage, Hinging, and Options .

Equipped with one NEMA 5-15P Plug

