



BEVERAGE-AIR

Project: _____	AIA# _____
Item: _____	
Location: _____	SIS# _____
Approved: _____	

REACH-IN BLAST CHILLER R290

RBS-162-SA-HC Solid Door Self-Contained Blast Chiller

MODEL:
RBS-162-SA-HC

RBS-162-SA-HC BLAST CHILLER/SHOCK REACH-IN FREEZER



3 Year Parts/Labor Warranty
5 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel exterior and interior
- Die-formed interior floor has rounded corners
- Central drain for easy cleaning
- Anti-condensation perimeter heating around door opening
- Ergonomic vertical door handle and stainless steel
- Snap in place magnetic gaskets self closing door with hold open stop at 100°
- Soft and hard, timed or core probe blast chilling
- Soft and hard, timed or core probe shock freezing
- Automatic recognition of core probe
- Multi point sensor temperature display button
- Core probe heater button
- HACCP alarm display button
- Pre-cooling cycle button
- Adjustable evaporator fan speed button
- Timed manual defrost button
- USB data recorder
- Infinity mode program with adjustable set point
- Automatic conservation mode at end of cycle
- On board recipe book with 68 pre-set programs
- 99 Free memory positions for custom programs
- LCD illuminated temperature display
- Unit comes standard with sixteen (16) wire rod tray slides
- Real time clock
- One, high precision heated multi sensor probe
- Stainless steel feet

OPTIONS & ACCESSORIES

- Single sensor probes (up to 4 possible)
- Change door swing
- Casters with brakes

REFRIGERATION SYSTEM

- Self-contained refrigeration system uses R290 refrigerant to comply with all environmental concerns
- Evaporator fitted with a high flow rate fan insures maximum cooling efficiency
- Indirect air flow assures highest product quality
- Manual defrosting with door open on a timed cycle
- Blast chilling (194°F to 37°F in 90 minutes) or shock freezing (194°F to 0°F in 240 minutes) cycles



Please verify qualifying units by visiting:
www.energystar.gov/cfs

3779 Champion Blvd., Winston-Salem, NC 27105
1-888-845-9800 Fax: 1-336-245-6453
Beverage-Air.com Sales@bevair.com




BEVERAGE-AIR®

MODEL	RBS-162-SA-HC
EXTERNAL DIMENSIONAL DATA	
Width Overall (in)	33.46"
Depth Overall (in)	39.37"
Height Overall (in)	77.17"
Number of Doors	1
Width, Door Opening 90° (in)	34"
Door Opening (in)	28.74" x 44.49"
PERFORMANCE DATA	
Sheet Pan Capacity (18" x 26") (pans not included)	16
Steam Table Pan Capacity (12" x 20") (pans not included)	16
Chilling Capacity In 90 Min	140 lbs
Freezing Capacity In 240 Min	100 lbs
Climate Class	5
ELECTRICAL DATA	
Cabinet Voltage	208-240/60/3
Total Amperes	13.2
NEMA Plug	15-20P
REFRIGERATION DATA	
Condensing Unit Size, HP	2 1/2
Refrigerant	R290
Capacity (BTU/HR) (113°F/-13°F)	9,154
Capacity (BTU/HR) (104°F/14°F)	19,485
WEIGHT DATA	
Gross Weight - Crated	648 lbs
Height - Crated	84"
Width - Crated	34"
Depth - Crated	40"


We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

Self-Contained Blast Chiller/Shock Reach-In Freezer Model: RBS-162-SA-HC


Model Views



PLAN VIEW



ELEVATION VIEW



SIDE VIEW

