

GHSS456RLB
 GHSS556RLB
 GHSS556RLB
 GHSS656RLB
 GHSS856RLB
 GHSS856RLB
 GHSS856RLB
 GHSS1056RLB
 GHSS1056RLB
 GHSS1256RLB
 GHSS1256RLB
 148-1/2"L x 43"D x 55-5/8"H

Included

- Remote DX refrigeration
- LED top & shelf lights
- One year parts & labor warranty
- · Stainless steel rear exterior
- Warmest average product temperature of 40°F or less



Specify	Standard Features	Additional Options					
EXTERIOR COLOR	Laminate (stock colors)	Laminate (non-stock colors)					
		Powder coated (stock/non-stock colors)					
		Powder coated Silversan Black					
		Stainless steel					
INTERIOR COLOR	Powder coated Silversan Black	Stainless steel					
LOWER FRONT PANEL COLOR	Powder coated Silversan Black	Powder coated (stock/non-stock colors)					
		Stainless steel					
BASE SUPPORT	Rail system for shims						
BUMPER FRONT	• 1" Boston bumper (specify color)	1" Stainless steel plate rail bumper					
END PANELS	Full w/stainless steel mirror interior	Cutaway w/ glass					
		None (specify per line-up)					
PRICE TAG MOLDING	• None	• 1" Price tag molding (black or silver)					
		Universal price tag molding (clear w/ open top)					
REAR DOORS	None (solid back panel)	Solid rear swinging door(s) w/lock					
SHELVING	• 8" & 12" & 16" & 20" Solid shelving	• 8" & 12" & 16" & 20" Glass shelving					
LIGHTS	LED 3500K w/ frosted lens	LED 4000K w/ frosted lens					
ELECTRICAL CONNECTION	Electrical leads (remote)						
REFRIGERATION	¹ • Remote DX refrigeration	Remote w/thermostat, solenoid & TXV					
SENSOR	• None	CPC discharge air sensor (remote)					
ACCESSORIES		Drain strainer					
		Night curtain, retractable, non-locking					
		Removable wire security cover, locking					

Std Notes: 1 - Read important notes for remote options

Option Notes: 1 - Read important notes for remote options

21873604


Structural Concepts

DELIVERING FRESH. ALWAYS.™

Intende	ed Environment:	Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.								
Zone	Intended Product To	Warmest Avg Prod Temp ° F								
1	Packaged refrigerate	d products	40							

PLAN VIEW OHSS456RLB = 24 3/8* OHSS656RLB = 30 1/2* OHSS656RLB GHSS56RLB GHSS656RLB GHSS56RLB GHSS65RLB GHSS65RLB GHSS65RLB GHSS56RLB GHSS65RLB GHSS65RLB GHSS65RLB GHSS65RLB GHSS65RLB GHSS56RLB GHSS65RLB GHSS66RLB GHS66RLB GHS66RLB GHS66RLB GHS66RLB GHS66RLB GHS66RLB GHS66RLB

SIDE VIEW



GHSS1056RLB, GHSS1256RLB CASE FRONT

NOTE: ALL DIMENSIONS APPROXIMATE

ELECTRICAL JUNCTION BOX
(SUPPLIED WITH 6" LEADS OR POWER CORD).

LOCATION OF DRAIN TUBE FOR REMOTE REF.
ONLY (SUPPLIED WITH 32" OR 112" PVC TUBE).

REFRIGERATION LINE CONNECTION.

REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

SELF-CONTAINED CASE SERVICE ACCESS AREA.

DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications																
Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
GHSS456RLB	48.75	51.00	3.50	Remote (DX)	Circuit #1	110-120	1	60	1.48	81	2+G	Leads Multiple	24.00	4579	4240	725
GHSS556RLB	60.63	62.88	3.50	Remote (DX)	Circuit #1	110-120	1	60	2.34	158	2+G	Leads Multiple	24.00	6696	6200	1,050
GHSS656RLB	73.13	75.38	3.50	Remote (DX)	Circuit #1	110-120	1	60	2.62	218	2+G	Leads Multiple	24.00	7646	7080	925
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	2.62	193	2+G	Leads Multiple	24.00	7646	7080	
GHSS856RLB	97.50	99.75	3.50	Remote (DX)	Circuit #1	110-120	1	60	3.67	225	2+G	Leads Multiple	24.00	10152	9400	1,250
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	3.67	210	2+G	Leads Multiple	-	10152	9400	
GHSS1056RLB	121.13	123.38	40.50	Remote (DX)	Circuit #1	110-120	1	60	3.04	188	2+G	Leads Multiple	20.00	13392	12400	1,300
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	3.04	188	2+G	Leads Multiple	20.00	13392	12400	
GHSS1256RLB	146.25	148.50	45.13	Remote (DX)	Circuit #1	110-120	1	60	4.51	338	2+G	Leads Multiple	24.00	15228	14100	1,500
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	4.51	374	2+G	Leads Multiple	24.00	10800	10000	
				Remote (R744 TRANSCRIT	Circuit #1	110-120	1	60	4.51	338	2+G	Leads Multiple		15228	14100	

*** Does not include electric defrost on freezer models.



In Accordance with AHRI Std 1200

DOE 2017 Energy Efficiency Compliant

Important Notes:

- 1) REMOTE REFRIGERATION NOTE: Condensing unit not included, floor drain required.
- 2) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle.
- 3) 45" minimum door entry clearance required (without shipping skid).
- 4) Units must be shimmed during installation to ensure the unit is level and plumb.

★ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.