



PR60B-D4

60" Pizza Prep Table with Drawers



PR60B-D4
06/27/25
Item # 13673

W x D x H

60" x 33.25" x 43.25"*

*to work surface with 6" casters



Dimensions / Capacity

Two-Section PR60B-D4

Interior Storage Capacity (CF) (AHAM)	16.63ft ³
Overall Width x Depth	60" x 33.25"
Height (including 6" casters)	43.25"
Depth with Cutting Board Installed (including 1" bumper)	36.25"
Depth with Drawer Fully Open (including 1" bumper)	57.5"
Pan Capacity (# of 1/3rd size x 4" or 6" deep)	8
Maximum Pan Depth	6"
Crated Weight	450 lbs.
Crated Length x Width x Height	63.75" x 35.75" x 45"

Electrical / Refrigeration

Two-Section PR60B-D4

Voltage	115/60/1
HACR Breaker	15.0 Amps
Electrical Connection (NEMA)	5-15P ⚡
Voltage Range	104-126
Ambient Temp. Range	45° to 100°F
Control Setpoint Range	16° to 36°F (rail) / 28° to 40°F (cabin)
Amperage	4
Energy Consumption (kWh/day) @NSF	5.63
Heat Rejection (BTU/Hr.) @NSF	801
Approx. Nominal Compres. BTU/HR (HP)	2431(1/3HP)
Refrigerant / Charge Amount (oz)	R290 (2.4 oz)

Options

- | | |
|---|---|
| ☐ 2" Casters (HS-5037, set of 4) | ☐ Drawer divider bar (HS-4007, Vertical) |
| ☐ 4" Casters (HS-5320, set of 4) | ☐ Stainless steel back panel (factory request) |
| ☐ Overshelves (HS-5639, single) | ☐ Drawer locks (factory request) |
| ☐ Overshelves (HS-5640, double) | ☐ Reversible door (factory request) |
| ☐ Pan divider kit for rail | |



Seven year warranty on labor, parts, and compressor. Valid in United States, Canada, Puerto Rico and U.S. Territories.

For more information, please visit hoshizakiamerica.com/support/warranty/

Item #: _____
Project: _____
Qty: _____
AIA#: _____

Features

- Dual controller system for ideal temperatures in both rail and cabinet
- Improved airflow from back to front of the rail for more even cooling of all pans in the rail
- Night/Day Mode- when lid is open set point drops to keep food cool in rail; when lid is closed set point returns to normal so food can stay in rail overnight without freezing

- Engineered to maintain NSF-7 temperatures in 100°F ambient. (Certified to NSF-7 temperatures in 86°F ambient.)
- Environmentally friendly R290 hydrocarbon refrigerant
- Stainless steel exterior front, sides and top with stainless steel interior sides, back and floor.
- Front breathing air flow design with removable louver for easy air filter cleaning
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- Rail utilizes a unique ducted air distribution system to distribute air evenly and maintain product temperature
- Cabinet and drawers are insulated with 2" of CFC free, foamed in place polyurethane
- Drawer slides are constructed of 14 gauge stainless steel with acetal rollers
- Drawer frames are constructed of 16 gauge stainless steel and securely fastened to cabinet
- Drawers have a 250 lb. dynamic load rating
- Drawers will accommodate (2) 12" x 10" x 6" and (2) 12" x 6" x 6" deep pans (pans by others)
- Provided with a full complement of polycarbonate plastic 1/3rd size pans, 4" deep and adapter bars
- Extruded aluminum flush mount drawer handle
- Magnetic drawer gasket is easily removable for cleaning
- 60" x 19" x 1/2" thick white polyethylene cutting board is standard
- Evaporator coils are epoxy electrocoated (E-Coat) to help fight corrosion
- Standard with 6" casters (two with brakes)
- 10 ft. cord and plug

If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle

