PANEL METERS

Easily monitor the internal temperature of your coolers and freezers without use in walk-in refrigerators, display cases, holding and specialty cabinets, dairy

- RETRO-FIT APPLICATIONS
- REMOTE INTERIOR TEMPERATURE READINGS

	DM120	DM120S-0-3
	Front Flange, Back Connect	Back Flange, Back Connect
Temperature Range:	-40° to 120°F (-40° to 48°C)	-40° to 120°F (-40° to 48°C)
Accuracy:	±2°F (±1°C)	±2°F (±1°C)
Resolution:	0.1°	0.1°
Ambient Operating Range:	15° to 150°F up to 90% non-condensing	15° to 150°F up to 90% non-condensing
Response Time:	30 second updates	30 second updates
LCD:	1.3” x 0.5” (33 mm x 13 mm)	1.3” x 0.5” (33 mm x 13 mm)
Lead Length:	39” (1 m)	39” (1 m)
Case Material:	Stainless Steel	Stainless Steel
Case Dimensions:	3.0” x 1.375” (76 mm x 27 mm)	3.47” x 1.1” (88 mm x 28 mm)
Power:	(1) 1.5V #LR754	(1) 1.5V #LR754
Mounting:	Front Flange	Back Flange
Weight:	2.5 oz (71 g)	3.5 oz (999 g)
Regulatory Listings:	CE NSF RoHS	CE NSF RoHS
Warranty:	1 year	1 year

	6142-13
	Front Flange, Back Connect
Temperature Range:	-40° to 120°F (-40 to 50°C)
Accuracy:	±2°F (±1°) at 10° and 40°F (-12° and 4.5°C) ±5°F (±2.5°C) at 110°F (43°C)
Dial Dimension:	2” (51 mm)
Capillary Length:	48” (1.2 m)
Case Material:	Stainless Steel
Flange:	Front
Connection:	Back
Mounting:	Flush
Weight:	5 oz (142 g)
Regulatory Listings:	RoHS
Warranty:	1 year