

# DISPLAY REFRIGERATOR

## Model: 2RENSGD

Natural Refrigerant R-290 Model

### 2-Section Extra-Wide Display Reach-In Refrigerator with Sliding Glass Doors

**2RENSGD** - Stainless steel front, aluminum end panels and interior

**2RENSASGD** - Stainless steel exterior, aluminum interior

**2RENSSSGD** - Stainless steel exterior and interior

**Designed to maintain NSF-7 temperatures in 100°F ambient.**



## Options and Accessories

(upcharge and lead times may apply)

|                                       |                                                      |
|---------------------------------------|------------------------------------------------------|
| Stainless steel case back             | Universal pan slides                                 |
| Additional epoxy coated steel shelves | Adjustable legs                                      |
| Chrome or stainless steel shelves     | Expansion valve                                      |
| Heavy duty pilaster strips            | Special electrical requirements<br>(consult factory) |
| Wine rack                             |                                                      |

Consult factory for other model configurations, options and accessories.

**Continental**  
Refrigerator



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

## Standard Model Features

### REFRIGERATION SYSTEM

Self contained, performance rated refrigeration system

Natural, environmentally safe,  
high efficiency R-290 refrigerant<sup>1</sup>

Automatic, electric condensate evaporator

### CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Double-pane, tempered sliding glass doors

Snap in door wiper

Door locks

Self-closing doors

Heavy duty, epoxy coated steel shelves

5" casters

### MODEL FEATURES

LED interior lighting

Electronic control, off cycle defrost

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

|                                                    |                  |
|----------------------------------------------------|------------------|
| Net Capacity (cubic feet)                          | 50 (1270 l)      |
| Width, Overall (inches)                            | 57 (1448 mm)     |
| Depth, Overall (inches)<br>(including grill)       | 34 ( mm)         |
| Depth (inches) (less grill)                        | 32 (813 mm)      |
| Clear Door Width (inches)                          | 21 7/8 (556 mm)  |
| Clear Door Height (inches)                         | 54 3/4 (1391 mm) |
| Height, Overall (inches)<br>(including 5" casters) | 82 1/4 (2089 mm) |
| Number of Doors                                    | 2                |
| Number of Shelves                                  | 8                |
| Shelf Area (square feet)                           | 44.5 (4.1 sq m)  |
| Tray Slide Capacity (per section)<br>(2" centers)  | 24               |

### REFRIGERANT DATA

|                             |      |
|-----------------------------|------|
| Condensing Unit Size (H.P.) | 1/3  |
| Capacity (BTU per hour)*    | 2540 |

### ELECTRICAL DATA

|                                                |                     |
|------------------------------------------------|---------------------|
| Voltage (International)                        | 115/60/1 (220/50/1) |
| Feed Wires (including ground)                  | 3                   |
| Total Amps (International)                     | 8.4 (5.1)           |
| 10 ft. Cord/Plug [attached]<br>(International) | Yes<br>(No)         |

### SHIPPING DATA



|                              |                  |
|------------------------------|------------------|
| Height - Crated (inches)     | 85 1/2 (2172 mm) |
| Width - Crated (inches)      | 64 (1626 mm)     |
| Depth - Crated (inches)      | 42 (1067 mm)     |
| Volume - Crated (cubic feet) | 133 (3766 cu l)  |
| Weight Std - Crated (pounds) | 490 (223 kg)     |
| Weight SS - Crated (pounds)  | 588 (267 kg)     |

\* Rating @ +25°F evaporator, 90°F ambient  
Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug  
(varies by country)

## Model Plan Views



**IMPORTANT NOTE:** If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides and rear.

**Continental**  
Refrigerator

Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunksferry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



PROUDLY  
DESIGNED & ASSEMBLED  
IN THE U.S.A.

© Copyright 2021. Continental Refrigerator.  
A Division of National Refrigeration & Air Conditioning Products, Inc.

REVISED: 9/18/25